# MINUTES OF KU-RING-GAI PLANNING PANEL HELD ON WEDNESDAY, 30 APRIL 2008

Present: Bill Tsakalos (Chairperson)

Kerry Bedford Vince Berkhout

Staff Present: General Manager (John McKee)

Manager Development Assessment Services (Corrie Swanepoel)

Senior Governance Officer (Geoff O'Rourke)

The Meeting commenced at 5.04pm

#### PP19 APOLOGIES

File: S06347

Ms Elizabeth Crouch tendered an apology for non-attendance and requested leave of absence.

# Resolved:

That the apology by Ms Elizabeth Crouch for non-attendance be accepted and leave of absence be granted.

#### **CARRIED UNANIMOUSLY**

# **DECLARATIONS OF INTEREST**

The Chairperson adverted to the necessity for Ku-ring-gai Planning Panel Members and staff to declare a Pecuniary Interest/Conflict of Interest in any item on the Business Paper.

No Interest was declared.

#### **CONFIRMATION OF MINUTES**

# PP20 Minutes of Ku-ring-gai Planning Panel

File: S06347

Meeting held 9 April 2008 Minutes numbered PP14 to PP18

# Resolved:

(Moved: Vince Berkhout/Bill Tsakalos)

That Minutes numbered PP14 to PP18 circulated to Panel members were taken as read and confirmed as an accurate record of the proceedings of the Meeting.

#### **CARRIED UNANIMOUSLY**

#### **GENERAL BUSINESS**

# PP21 16 to 22 Stonecrop Road, North Turramurra - Demolition of Existing & Subdivision into 8 Lots

File: DA1315/07

Ward: Wahroonga

Applicant: Ronald Mah-Chut

Owner: Three Crowns Investments Pty Ltd

#### The following member of the public addressed the Panel:

# R Wagner

To determine development application No 1315/07 for subdivision of the site into 8 allotments

# Resolved:

(Moved: Vince Berkhout/Kerry Bedford)

# Pursuant to Section 80(1) of the Environmental Planning and Assessment Act, 1979

That Development Application No. 1315/07 for demolition of existing dwelling and associated structures and Torrens Title subdivision of one lot into 8 lots at No.16 to 22 Stonecrop Road, North Turramurra, be approved for a period of two (2) years from the dated of the Notice of Determination, subject to the following conditions:

#### The conditions of consent are as follows:

# **CONDITIONS THAT IDENTIFY APPROVED PLANS:**

# 1. Approved architectural plans and documentation (new development)

The development must be carried out in accordance with the following plans and documentation listed below and endorsed with Council's stamp, except where amended by other conditions of this consent:

Plan no.	Drawn by	Dated
11188 - SL - 4, Sheet 1 of 1	Hammond Smeallie &	17 March 2006
	Co. Pty Ltd	

**Reason:** To ensure that the development is in accordance with the determination.

# CONDITIONS TO BE SATISFIED PRIOR TO DEMOLITION, EXCAVATION OR CONSTRUCTION:

# 2. Preservation of Endangered Ecological Community (TSC Act 1995 (NSW))

The following recommendations made in Section 6.2, Flora and Fauna Assessment, prepared by Footprint Green, dated 6 November 2007, are required to be carried out as part of the landscape works for the site.

- 1. Removal of the existing *Nerium Oleander* (Oleander) from the road reserve affronting the allotment.
- Planting of endemic species on the road reserve refer separate condition.

**Reason:** To preserve and enhance the Duffy's Forest community on the site.

#### 3. Duplicated condition deleted

#### 4. Notice of commencement

At least 48 hours prior to the commencement of any development (including excavation, shoring or underpinning works), a notice of commencement of building or subdivision work form and appointment of the principal certifying authority form shall be submitted to Council.

**Reason:** Statutory requirement.

# 5. Notification of builder's details

Prior to the commencement of any development or excavation works, the Principal Certifying Authority shall be notified in writing of the name and contractor license number of the owner/builder intending to carry out the approved works.

**Reason:** Statutory requirement.

# 6. Dilapidation survey and report (public infrastructure)

Prior to the commencement of any development or excavation works on site, the Principal Certifying Authority shall be satisfied that a dilapidation report on the visible and structural condition of all structures of the following public infrastructure, has been completed and submitted to Council:

#### **Public infrastructure**

- Full road pavement width, including kerb and gutter, of Stonecrop road over the site frontage.
- All driveway crossings and laybacks opposite the subject site.

The report must be completed by a consulting structural/civil engineer. Particular attention must be paid to accurately recording (both written and photographic) existing damaged areas on the aforementioned infrastructure so that Council is fully informed when assessing any damage to public infrastructure caused as a result of the development.

The developer may be held liable to any recent damage to public infrastructure in the vicinity of the site, where such damage is not accurately recorded by the requirements of this condition prior to the commencement of works.

Note: A written acknowledgment from Council must be obtained (attesting

to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any

excavation works.

**Reason:** To record the structural condition of public infrastructure before

works commence.

# 7. Construction and traffic management plan

Prior to the commencement of any works on site, the applicant must submit for review by Council's engineers a construction and traffic management plan. The following matters must be specifically addressed in the plan:

#### 1. A plan view of the entire site and frontage roadways indicating:

- dedicated construction site entrances and exits, controlled by a certified traffic controller, to safely manage pedestrians and construction related vehicles in the frontage roadways
- turning areas within the site for construction and spoil removal vehicles, allowing a forward egress for all construction vehicles on the site
- the locations of proposed work zones in the frontage roadways
- location of any proposed crane and concrete pump and truck standing areas on and off the site
- a dedicated unloading and loading point within the site for all construction vehicles, plant and deliveries
- material, plant and spoil bin storage areas within the site, where all materials are to be dropped off and collected
- an on-site parking area for employees, tradespersons and construction vehicles as far as possible

# 2. Traffic control plan(s) for the site

All traffic control plans must be in accordance with the RTA publication "Traffic Control Worksite Manual" and prepared by a suitably qualified person (minimum 'red card' qualification). The main stages of the

development requiring specific construction management measures are to be identified and specific traffic control measures identified for each stage.

Approval is to be obtained from Council for any temporary road closures or crane use from public property. Applications to Council shall be made a minimum of 4 weeks prior to the activity proposed being undertaken.

# 3. A detailed description and route map of the proposed route for vehicles involved in spoil removal, material delivery and machine floatage must be provided

Light traffic roads and those subject to a load or height limit must be avoided where alternate routes exist.

A copy of this route is to be made available to all contractors and shall be clearly depicted at a location within the site.

The plan must provide evidence of RTA concurrence where construction access is provided directly from or within 20m of an arterial road.

The plan must provide a schedule of site inductions to be held on regular occasions and as determined necessary to ensure all new employees are aware of their construction management obligations. These must specify that construction-related vehicles are to comply with the approved requirements.

The plan must provide measures for minimising construction related traffic movements during school peak periods.

For those construction personnel that drive to the site, the applicant shall attempt to provide on-site parking so that their personnel's vehicles do not impact on the current parking demand in the area.

The construction and traffic management plan shall be prepared by a suitably qualified and experienced traffic consultant and be certified by this person as being in accordance with the requirements of the abovementioned documents and the requirements of this condition. The construction management measures contained in the approved plan shall be implemented in accordance with the plan prior to the commencement of, and during, works on-site including excavation.

As the plan has a direct impact on the local road network, the plan shall be submitted to and reviewed by Council's Development Engineer. Written acknowledgment from Council's Engineer shall be obtained (attesting to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any works on site.

Reason:

To ensure that appropriate measures have been considered during all phases of the construction process in a manner that maintains the environmental amenity and ensures the ongoing safety and protection of people.

#### 8. Temporary construction exit

A temporary construction exit, together with necessary associated temporary fencing, shall be provided prior to commencement of any work on the site and shall be maintained throughout the duration and progress of construction.

**Reason:** To reduce or eliminate the transport of sediment from the construction site onto public roads.

#### 9. Sediment controls

Prior to any work commencing on site, sediment and erosion control measures shall be installed along the contour immediately downslope of any future disturbed areas.

The form of the sediment controls to be installed on the site shall be determined by reference to the 'NSW Department of Housing manual 'Managing Urban Stormwater: Soils and Construction'. The erosion controls shall be maintained in an operational condition until the development activities have been completed and the site fully stabilised. Sediment shall be removed from the sediment controls following each heavy or prolonged rainfall period.

**Reason:** To preserve and enhance the natural environment.

#### 10. Tree protection fencing

To preserve the following tree/s, no work shall commence until the area beneath their canopy is fenced off at the specified radius from the trunk/s to prevent any activities, storage or the disposal of materials within the fenced area. The fence/s shall be maintained intact until the completion of all demolition/building work on site.

# Schedule Tree/location

All trees on site not approved to be removed – Trees 6, 9-11, 15-20, 23-26, 30-38, 40-50, 52-54

All trees on adjoining sites – Trees 27, 28, 51

#### Radius in metres

No closer than the Optimal Tree Protection Zone (refer Table 6.1, Arboricultural Assessment Footprint Green, 27/02/08) No closer than the Optimal Tree Protection Zone (refer Table 6.1, Arboricultural Assessment Footprint Green, 27/02/08)

**Reason:** To protect existing trees during the construction phase.

# 11. Tree Protective Fencing Type Galvanised Mesh

The tree protection fencing shall be constructed of galvanised pipe at 2.4 metre spacings and connected by securely attached chain mesh fencing to a minimum of 1.8 metres in height prior to work commencing.

**Reason:** To protect existing trees during construction phase.

#### 12. Tree protection signage

Prior to works commencing, tree protection signage is to be attached to each tree protection zone, displayed in a prominent position and the sign repeated at 10 metres intervals or closer where the fence changes direction. Each sign shall contain in a clearly legible form, the following information:

- tree protection zone
- this fence has been installed to prevent damage to the trees and their growing environment both above and below ground and access is restricted
- any encroachment not previously approved within the tree protection zone shall be the subject of an arborist's report
- the arborist's report shall provide proof that no other alternative is available
- the arborist's report shall be submitted to the Principal Certifying Authority for further consultation with Council
- The name, address, and telephone number of the developer.

**Reason:** To protect existing trees during the construction phase.

# 13. Tree fencing inspection

Upon installation of the required tree protection measures, an inspection of the site by the Principal Certifying Authority is required to verify that tree protection measures comply with all relevant conditions.

**Reason:** To protect existing trees during the construction phase.

# CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF THE CONSTRUCTION CERTIFICATE:

#### 14. Long service levy

In accordance with Section 109F(i) of the Environmental Planning and Assessment Act a Construction Certificate shall not be issued until any long service levy payable under Section 34 of the Building and Construction Industry Long Service Payments Act 1986 (or where such levy is payable by instalments, the first instalment of the levy) has been paid. Council is authorised to accept payment. Where payment has been made elsewhere, proof of payment is to be provided to Council.

**Reason:** Statutory requirement.

#### 15. Builder's indemnity insurance

The applicant, builder, developer or person who does the work on this development, must arrange builder's indemnity insurance and submit the certificate of insurance in accordance with the requirements of Part 6 of the Home Building Act 1989 to the Certifying Authority for endorsement of the plans

accompanying the Construction Certificate.

It is the responsibility of the applicant, builder or developer to arrange the builder's indemnity insurance for residential building work over the value of \$12,000. The builder's indemnity insurance does not apply to commercial or industrial building work or to residential work valued at less than \$12,000, nor to work undertaken by persons holding an owner/builder's permit issued by the Department of Fair Trading (unless the owner/builder's property is sold within 7 years of the commencement of the work).

**Reason:** Statutory requirement.

#### 16. Stormwater management plan

Prior to issue of the Construction Certificate, the applicant must submit, for approval by the Principal Certifying Authority, scale construction plans and specifications in relation to the stormwater management and disposal system for the development. The plan(s) must include the following detail:

- exact location and reduced level of discharge point to the public drainage system
- details of the required on-site detention tanks required by Ku-ring-gai Water Management DCP 47, including dimensions, materials, locations, orifice and discharge control pit details as required (refer Chapter 6 and Appendices 2, 3 and 5 of DCP 47 for volume, PSD and design requirements)

The above construction drawings and specifications are to be prepared by a qualified and experienced civil/hydraulic engineer in accordance with Council's Water Management Development Control Plan 47, Australian Standards 3500.2 and 3500.3 - Plumbing and Drainage Code and the Building Code of Australia. The plans may be generally based on the **Stormwater Plan SW 0829 Rev. 'A' dated 3/907** prepared by **Greg Timewell & Associates** submitted with the development application, which are to be advanced as necessary for construction certificate issue purposes.

**Reason:** To protect the environment.

#### 17. Stormwater detention

Prior to the issue of a Construction Certificate, the Principal Certifying Authority is to be satisfied that an on-site stormwater detention system must be provided to control the rate of runoff leaving the site. The minimum volume of the required on-site detention system must be determined in accordance with Chapter 6 of the Ku-ring-gai Council Water Management Development Control Plan 47 - having regard to the specified volume concession offered in lieu of installing rainwater retention tanks. The on-site detention system must be designed by a qualified civil/hydraulic engineer and must satisfy the design controls set out in Appendix 5 of DCP 47.

**Reason:** To protect the environment.

#### 18. Excavation for services

Prior to the issue of the Construction Certificate, the Principal Certifying shall be satisfied that no proposed underground services (ie. water, sewerage, drainage, gas or other service) unless previously approved by conditions of consent, are located beneath the canopy of any tree protected under Council's Tree Preservation Order, located on the subject allotment and adjoining allotments.

**Note:** A plan detailing the routes of these services and trees protected

under the Tree Preservation Order, shall be submitted to the

Principal Certifying Authority.

**Reason:** To ensure the protection of trees.

#### 19. Design of works in public road (Roads Act approval)

Prior to issue of the Construction Certificate, the Certifying Authority shall be satisfied that engineering plans and specifications prepared by a qualified consulting engineer have been approved by Council's Development Engineer. The plans to be assessed must be to a detail suitable for construction issue purposes and must detail the infrastructure works for the road shoulder with kerb and gutter for the frontage of the property in Stonecrop Road.

Development consent does not give approval to these works in the road reserve. The applicant must obtain a separate approval under sections 138 and 139 of The Roads Act 1993 for the works in the road reserve required as part of the development. The Construction Certificate must not be issued, and these works must not proceed until Council has issued a formal written approval under the Roads Act 1993.

The required plans and specifications are to be designed in accordance with the General Specification for the Construction of Road and Drainage Works in Kuring-gai Council, dated November 2004. The drawings must detail existing utility services and trees affected by the works, erosion control requirements and traffic management requirements during the course of works. Survey must be undertaken as required. Traffic management is to be certified on the drawings as being in accordance with the documents SAA HB81.1 – 1996 – Field Guide for Traffic Control at Works on Roads – Part 1 and RTA Traffic Control at Work Sites (1998). Construction of the works must proceed only in accordance with any conditions attached to the Roads Act approval issued by Council.

A minimum of three (3) weeks will be required for Council to assess the Roads Act application. Early submission of the Roads Act application is recommended to avoid delays in obtaining a Construction Certificate. An engineering assessment and inspection fee (set out in Council's adopted fees and charges) is payable and Council will withhold any consent and approved plans until full payment of the correct fees. Plans and specifications must be marked to the attention of Council's Development Engineers. In addition, a copy of this condition must be provided, together with a covering letter stating the full address of the property and the accompanying DA number.

**Reason:** To ensure that the plans are suitable for construction purposes.

#### 20. Energy Australia requirements

Prior to issue of the Construction Certificate, the applicant must contact Energy Australia regarding power supply for the subject development. A written response detailing the full requirements of Energy Australia (including any need for underground cabling, substations or similar within or in the vicinity the development) shall be submitted to the Principal Certifying Authority for approval prior to issue of the Construction Certificate.

Any structures or other requirements of Energy Australia shall be indicated on the plans issued with the Construction Certificate, to the satisfaction of the Principal Certifying Authority and Energy Australia. The requirements of Energy Australia must be met in full prior to issue of the Occupation Certificate.

**Reason:** To ensure compliance with the requirements of Energy Australia.

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF THE CONSTRUCTION CERTIFICATE OR PRIOR TO DEMOLITION, EXCAVATION OR CONSTRUCTION (WHICHEVER COMES FIRST):

#### 21. Infrastructure restorations fee

To ensure that damage to Council Property as a result of construction activity is rectified in a timely matter:

- a) All work or activity taken in furtherance of the development the subject of this approval must be undertaken in a manner to avoid damage to Council Property and must not jeopardise the safety of any person using or occupying the adjacent public areas.
- b) The applicant, builder, developer or any person acting in reliance on this approval shall be responsible for making good any damage to Council Property and for the removal from Council Property of any waste bin, building materials, sediment, silt, or any other material or article.
- c) The Infrastructure Restoration Fee must be paid to the Council by the applicant prior to both the issue of the Construction Certificate and the commencement of any earthworks or construction.
- d) In consideration of payment of the Infrastructure Restorations Fee, Council will undertake such inspections of Council Property as Council considers necessary and also undertake, on behalf of the applicant, such restoration work to Council Property, if any, that Council considers necessary as a consequence of the development. The provision of such restoration work by the Council does not absolve any person of the responsibilities contained in (a) to (b) above. Restoration work to be undertaken by the Council referred to in this condition is limited to work that can be undertaken by Council at a cost of not more than the Infrastructure Restorations Fee payable pursuant to this condition.

#### e) In this condition:

"Council Property" includes any road, footway, footpath paving, kerbing, guttering, crossings, street furniture, seats, letter bins, trees, shrubs, lawns, mounds, bushland, and similar structures or features on any road or public road within the meaning of the Local Government Act 1993 (NSW) or any public place; and

"Infrastructure Restoration Fee" means the Infrastructure Restorations Fee calculated in accordance with the Schedule of Fees & Charges adopted by Council as at the date of payment and the cost of any inspections required by the Council of Council Property associated with this condition.

**Reason**: To maintain public infrastructure.

# 22. Section 94 contributions – residential development

A contribution pursuant to section 94 of the Environmental Planning and Assessment Act as specified in Ku-ring-gai Section 94 Contributions Plan 2004-2009 for the services detailed in column A and for the amount detailed in Column B is required.

Column A	Column B
community facilities	\$428.78
park acquisition and embellishment works	\$4,481.40 + \$124.86
park embellishment works	\$595.60 + \$438.64
sportsgrounds works	\$1,463
aquatic / leisure centres	\$86.63
traffic and transport	\$122.22
section 94 Plan administration	\$109.56
Total:	\$7850.69 x 3.48 (persons per lot)
Sub total:	\$27,320.40 x 7 (lots)
Grand total:	\$191,242.80

The contribution shall be paid to Council prior to the commencement of any development (including demolition) or prior to the issue of the Construction Certificate (whichever comes first). The charges may vary at the time of payment in accordance with Council's Section 94 Contributions Plan to reflect changes in land values, construction costs and the consumer price index. Prior to payment, you are advised to check the contribution amount required with Council.

**Reason:** To ensure the provision, extension or augmentation of community facilities, recreation facilities, open space and administration that

will, or are likely to be, required as a consequence of the

development.

# CONDITIONS TO BE SATISFIED DURING THE DEMOLITION, EXCAVATION AND **CONSTRUCTION PHASES:**

#### 23. Approved plans to be on site

A copy of all approved and certified plans, specifications and documents incorporating conditions of consent and certification (including the Construction Certificate if required for the work) shall be kept on site at all times during the demolition, excavation and construction phases and must be readily available to any officer of Council or the Principal Certifying Authority.

Reason: To ensure that the development is in accordance with the determination.

#### 24. **Engineering fees**

For the purpose of any development related inspections by Ku-ring-gai Council engineers, the corresponding fees set out in Councils adopted Schedule of Fees and Charges are payable to Council. A re-inspection fee per visit may be charged where work is unprepared at the requested time of inspection, or where remedial work is unsatisfactory and a further inspection is required. Engineering fees must be paid in full prior to any final consent from Council.

**Reason:** To protect public infrastructure.

#### Prescribed conditions 25.

The applicant shall comply with any relevant prescribed conditions of development consent under clause 98 of the Environmental Planning and Assessment Regulation. For the purposes of section 80A (11) of the Environmental Planning and Assessment Act, the following conditions are prescribed in relation to a development consent for development that involves any building work:

- The work must be carried out in accordance with the requirements of the Building Code of Australia
- In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of that Act, that such a contract of insurance is in force before any works commence.

**Reason:** Statutory requirement.

#### 26. Statement of compliance with Australian Standards

The demolition work shall comply with the provisions of Australian Standard AS2601: 2001 The Demolition of Structures. The work plans required by AS2601: 2001 shall be accompanied by a written statement from a suitably qualified person that the proposal contained in the work plan comply with the safety requirements of the Standard. The work plan and the statement of compliance shall be submitted to the satisfaction of the Principal Certifying Authority prior to the commencement of any works.

**Reason:** To ensure compliance with the Australian Standards.

#### 27. Demolition, excavation and construction work hours

Demolition, excavation, construction work and deliveries of building material and equipment must not take place outside the hours of 7.00am to 5.00pm Monday to Friday and 8.00am to 12.00pm Saturday. No work and no deliveries are to take place on Sundays and public holidays.

Excavation or removal of any materials using machinery of any kind, including compressors and jack hammers, must be limited to between 7.30am and 5.00pm Monday to Friday, with a respite break of 45 minutes between 12 noon and 1.00pm.

Where it is necessary for works to occur outside of these hours (i.e. concrete pours and standing of plant), approval for such will be subject to the issue of an "outside of hours works permit" from Council as well as notification of the surrounding properties likely to be affected by the proposed works.

**Note:** Failure to obtain a permit for work outside of the approved hours

will result in on the spot fines being issued.

Reason: To ensure reasonable standards of amenity for occupants of

neighbouring properties.

#### 28. Construction noise

During excavation, demolition and construction phases, noise generated from the site shall be controlled in accordance with the recommendations of the approved noise and vibration management plan.

**Reason:** To ensure reasonable standards of amenity to neighbouring

properties.

#### 29. Site notice

A site notice shall be erected on the site prior to any work commencing and shall be displayed throughout the works period.

The site notice must:

- be prominently displayed at the boundaries of the site for the purposes of informing the public that unauthorised entry to the site is not permitted
- display project details including, but not limited to the details of the builder, Principal Certifying Authority and structural engineer
- be durable and weatherproof
- display the approved hours of work, the name of the site/project manager, the responsible managing company (if any), its address and 24 hour contact phone number for any inquiries, including construction/noise complaint are to be displayed on the site notice
- be mounted at eye level on the perimeter hoardings/fencing and is to state that unauthorised entry to the site is not permitted.

**Reason:** To ensure public safety and public information.

#### 30. Dust control

During excavation, demolition and construction, adequate measures shall be taken to prevent dust from affecting the amenity of the neighbourhood. The following measures must be adopted:

- physical barriers shall be erected at right angles to the prevailing wind direction or shall be placed around or over dust sources to prevent wind or activity from generating dust
- earthworks and scheduling activities shall be managed to coincide with the next stage of development to minimise the amount of time the site is left cut or exposed
- all materials shall be stored or stockpiled at the best locations
- the ground surface should be dampened slightly to prevent dust from becoming airborne but should not be wet to the extent that run-off occurs
- all vehicles carrying spoil or rubble to or from the site shall at all times be covered to prevent the escape of dust
- all equipment wheels shall be washed before exiting the site using manual or automated sprayers and drive-through washing bays
- gates shall be closed between vehicle movements and shall be fitted with shade cloth
- cleaning of footpaths and roadways shall be carried out daily

**Reason:** To protect the environment and amenity of surrounding properties.

# 31. Post-construction dilapidation report

The applicant shall engage a suitably qualified person to prepare a post construction dilapidation report at the completion of the construction works. This report is to ascertain whether the construction works created any structural damage to adjoining buildings, infrastructure and roads. The report is to be submitted to the Principal Certifying Authority. In ascertaining whether adverse structural damage has occurred to adjoining buildings, infrastructure and roads, the Principal Certifying Authority must:

- compare the post-construction dilapidation report with the preconstruction dilapidation report
- have written confirmation from the relevant authority that there is no adverse structural damage to their infrastructure and roads.

A copy of this report is to be forwarded to Council at the completion of the construction works.

**Reason:** Management of records.

# 32. Use of road or footpath

During excavation, demolition and construction phases, no building materials, plant or the like are to be stored on the road or footpath without written

approval being obtained from Council beforehand. The pathway shall be kept in a clean, tidy and safe condition during building operations. Council reserves the right, without notice, to rectify any such breach and to charge the cost against the applicant/owner/builder, as the case may be.

**Reason:** To ensure safety and amenity of the area.

# 33. Guarding excavations

All excavation, demolition and construction works shall be properly guarded and protected with hoardings or fencing to prevent them from being dangerous to life and property.

Reason: To ensure public safety.

#### 34. Toilet facilities

During excavation, demolition and construction phases, toilet facilities are to be provided, on the work site, at the rate of one toilet for every 20 persons or part of 20 persons employed at the site.

Reason: Statutory requirement.

# 35. Protection of public places

If the work involved in the erection, demolition or construction of the development is likely to cause pedestrian or vehicular traffic in a public place to be obstructed or rendered inconvenient, or building involves the enclosure of a public place, a hoarding or fence must be erected between the work site and the public place.

If necessary, a hoarding is to be erected, sufficient to prevent any substance from, or in connection with, the work falling into the public place.

The work site must be kept lit between sunset and sunrise if it is likely to be hazardous to persons in the public place.

Any hoarding, fence or awning is to be removed when the work has been completed.

**Reason:** To protect public places.

#### 36. Road reserve safety

All public footways and roadways fronting and adjacent to the site must be maintained in a safe condition at all times during the course of the development works. Construction materials must not be stored in the road reserve. A safe pedestrian circulation route and a pavement/route free of trip hazards must be maintained at all times on or adjacent to any public access ways fronting the construction site. Where public infrastructure is damaged, repair works must be carried out when and as directed by Council officers. Where pedestrian circulation is diverted on to the roadway or verge areas, clear directional

signage and protective barricades must be installed in accordance with AS1742-3 (1996) "Traffic Control Devices for Work on Roads". If pedestrian circulation is not satisfactorily maintained across the site frontage, and action is not taken promptly to rectify the defects, Council may undertake proceedings to stop work.

**Reason:** To ensure safe public footways and roadways during construction.

#### 37. Services

Where required, the adjustment or inclusion of any new utility service facilities must be carried out by the applicant and in accordance with the requirements of the relevant utility authority. These works shall be at no cost to Council. It is the applicants full responsibility to make contact with the relevant utility authorities to ascertain the impacts of the proposal upon utility services (including water, phone, gas and the like). Council accepts no responsibility for any matter arising from its approval to this application involving any influence upon utility services provided by another authority.

**Reason:** Provision of utility services.

#### 38. Erosion control

Temporary sediment and erosion control and measures are to be installed prior to the commencement of any works on the site. These measures must be maintained in working order during construction works up to completion. All sediment traps must be cleared on a regular basis and after each major storm and/or as directed by the Principal Certifying Authority and Council officers.

**Reason:** To protect the environment from erosion and sedimentation.

# 39. Drainage to street

Stormwater runoff from all new impervious areas and subsoil drainage systems shall be piped to the street drainage system. New drainage line connections to the street drainage system shall conform and comply with the requirements of Sections 5.3 and 5.4 of Ku-ring-gai Water Management Development Control Plan No. 47.

**Reason:** To protect the environment.

#### 40. Sydney Water Section 73 Compliance Certificate

The applicant must obtain a **Section 73 Compliance Certificate** under the *Sydney Water Act 1994*. An application must be made through an authorised Water Servicing Co-ordinator. The applicant is to refer to "Your Business" section of Sydney Water's web site at <a href="https://www.sydneywater.com.au">www.sydneywater.com.au</a> then the "edevelop" icon or telephone 13 20 92. Following application a "Notice of Requirements" will detail water and sewer extensions to be built and charges to be paid. Please make early contact with the Co-ordinator, since building of water/sewer extensions can be time consuming and may impact on other services and building, driveway or landscape design.

**Reason:** Statutory requirement.

# 41. Trees on nature strip

Removal/pruning of the following tree/s from Council's nature strip to permit vehicular access shall be undertaken at no cost to Council by an experienced tree removal contractor/arborist holding public liability insurance amounting to a minimum cover of \$10,000,000.

# Schedule

#### Tree/location

Eucalyptus sieberi (Silvertop Ash)Tree 1, nature strip

**Reason:** To ensure protection of existing trees.

# 42. Temporary groundcover

On disturbed areas which will otherwise remain exposed for more than fourteen (14) days before permanent stabilisation works are undertaken, a temporary cover of mulch shall be applied or a dense cover crop shall be established utilising sterile/non seed-setting species.

**Reason:** To protect the environment.

#### 43. Stockpiling of top soil

Top soil shall be stripped from areas to be developed and stock-piled within the site. Stock-piled topsoil must be located outside drainage lines and tree canopies and be protected from run-on water by suitably positioned diversion banks. Where the period of storage will exceed fourteen (14) days, stock-piles are to be seeded or sprayed with an appropriate emulsion solution to minimise particle movement.

**Reason:** To protect the environment.

# 44. Treatment of tree roots

If tree roots are required to be severed for the purposes of constructing the approved works, they shall be cut cleanly by hand, by an experienced arborist/horticulturist with a minimum qualification of horticulture certificate or tree surgery certificate

**Reason:** To protect existing trees.

# 45. Approved tree works

Approval is given for the following works to be undertaken to trees on the site:

#### **Schedule**

Tree location	Approved tree works
Eucalyptus sieberi (Silvertop Ash) Tree 1, nature strip	Removal
Pinus pinaster (Maritime Pine) Tree 2	Removal
Corymbia gummifera (Red Bloodwood) Tree 3	Removal
Corymbia gummifera (Red Bloodwood) Tree 4	Removal
Eucalyptus sieberi (Silvertop Ash) Tree 5	Removal
Eucalyptus sieberi (Silvertop Ash) Tree 5	Removal

Removal or pruning of any other tree on the site is not approved.

**Reason:** To ensure that the development is in accordance with the

determination.

#### 46. Excavation near trees

No mechanical excavation shall be undertaken within the specified radius of the trunk(s) of the following tree(s) until root pruning by hand along the perimeter line of such works is completed:

# Schedule

# Tree/location

#### Radius from trunk

9m

Pinus radiata (Monterey Pine)Tree 32

**Reason:** To protect existing trees.

# 47. No storage of materials beneath trees

No activities, storage or disposal of materials shall take place beneath the canopy of any tree protected under Council's Tree Preservation Order at any time.

**Reason:** To protect existing trees.

# 48. Tree planting on nature strip

The following tree species shall be planted, at no cost to Council, in the nature strip fronting the property along Stonecrop Road. The tree(s) used shall be minimum 25 litres container size specimen(s):

Schedule Tree/ species	Quantity	Location
Eucalyptus haemastoma (Scribbly Gum)	2	Stonecrop Road – minimum 4m from
Eucalyptus sieberi (Silvertop Ash)	2	proposed driveway Stonecrop Road – minimum 4m from
Corymbia gummifera (Red Bloodwood)	2	proposed driveway Stonecrop Road – minimum 4m from proposed driveway

**Reason:** To provide appropriate landscaping within the streetscape.

#### 49. Tree removal on nature strip

Following removal of the *Eucalyptus sieberi* (Silvertop Ash) from Council's nature strip, the nature strip shall be rehabilitated to the satisfaction of Council's Landscape Assessment Officer at no cost to Council.

**Reason:** To protect the streetscape.

#### 50. Removal of refuse

All builders' refuse, spoil and/or material unsuitable for use in landscape areas shall be removed from the site on completion of the building works.

**Reason:** To protect the environment.

# 51. Archival recording of buildings

Prior to the commencement of any development or excavation works on site, the Principal Certifying Authority shall be satisfied that an archival report has been submitted to Council's Heritage Advisor.

The report must consist of an archival standard photographic record of the building (internally and externally), its garden and views of it from the street illustrating its relationship to neighbouring properties and the streetscape. Recording shall be undertaken in accordance with the guidelines for "Photographic Recording of Heritage Items Using Film or Digital Capture (2006)" prepared by the New South Wales Heritage Office.

Information shall be bound in an A4 report format. It shall include copies of photographs, referenced to plans of the site. Two (2) copies (one (1) copy to include negatives or CD of images shall be submitted to Council's Heritage Advisor. The recording document will be held in the local studies collection of Ku-ring-gai Library, the local historical society and Council's files.

**Note:** A written acknowledgment from Council must be obtained (attesting

to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any

works.

**Reason:** To ensure the proper management of historical artefacts and to

ensure their preservation.

# CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A SUBDIVISION CERTIFICATE:

# 52. WAE plans for stormwater management and disposal

Prior to issue of the Subdivision Certificate, a registered surveyor must provide a works as executed survey of the completed stormwater drainage and management systems. The survey must be submitted to and approved by the Principal Certifying Authority prior to issue of the Final Certificate.

The works as executed plan(s) must show the as built details above in comparison to those shown on the drainage plans approved with the Construction Certificate prior to commencement of works. All relevant levels and details indicated must be marked in red on a copy of the Principal Certifying Authority stamped construction certificate stormwater plans.

**Reason:** To protect the environment.

#### 53. Requirements of public authorities for connection to services

Prior to the issue of the Subdivision Certificate, the Principal Certifying Authority shall be satisfied that the applicant has complied with the requirements of any public authorities (e.g. Energy Australia, Sydney Water, Telstra Australia, AGL, etc) in regard to the connection, relocation and/or adjustment of the services affected by the proposed subdivision. All costs related to the relocation, adjustment or support of services are the responsibility of the applicant.

**Note:** Details of compliance with the requirements of any relevant public

authorities are to be submitted to the Principal Certifying Authority.

**Reason:** To ensure that services are available to the allotments of land.

# 54. Construction of works in public road

Prior issue of the Subdivision Certificate all road, footpath and/or drainage works in the public road must be completed in full, inspected and approved by Council. The applicant's designing engineer is to provide certification upon completion that the works were constructed in accordance with the Council approved drawings. This certification shall be provided prior to release of the linen plan/issue of the Subdivision Certificate. The completed works are to be approved by Council's Development Engineer prior to release of the linen plan/issue of the Subdivision Certificate.

**Reason:** To ensure completion of all road, footpath and/or drainage works in

the public road.

# 55. Infrastructure repair – subdivision works

Prior to issue of the Subdivision Certificate, any infrastructure within the road reserve along the frontage of the subject site or within close proximity, which has been damaged as a result of subdivision works, must be fully repaired to the satisfaction of Council's Development Engineer and at no cost to Council.

**Reason:** To protect public infrastructure

#### 56. Provision of services

Prior to issue of the Subdivision Certificate, separate underground electricity, gas and phone or appropriate conduits for the same, must be provided to each allotment to the satisfaction of the utility provider. A suitably qualified and

experienced engineer or surveyor is to provide certification that all new lots have ready underground access to the services of electricity, gas and phone. Alternatively, a letter from the relevant supply authorities stating the same may be submitted to satisfy this condition.

Reason: Access to public utilities.

#### 57. Submission of 88b instrument

Prior to the issue of the Subdivision Certificate, the applicant must submit an original instrument under Section 88B of the Conveyancing Act with the plan of subdivision, plus six (6) copies to Council. Ku-ring-gai Council must be named as the authority whose consent is required to release, vary or modify the burdens.

**Reason:** To create all required easements, rights-of-carriageway, positive

covenants, restrictions-on-use or other burdens/benefits as may be

required.

#### 58. Submission of plans of subdivision

For endorsement of the subdivision certificate, the applicant shall submit an original plan of subdivision plus 6 copies, suitable for endorsement by Council. The following details must be submitted with the plan of subdivision and its copies:

- the endorsement fee current a the time of lodgement
- the 88B instrument plus 6 copies
- all surveyor's and/or consulting engineers' certification(s) required under this subdivision consent
- The Section 73 (Sydney Water) Compliance Certificate for the subdivision.

Council will check the consent conditions on the subdivision. Failure to submit the required information will delay endorsement of the linen plan and may require payment of rechecking fees. Plans and copies of subdivision must not be folded. Council will not accept bonds in lieu of completing subdivision works.

**Reason:** Statutory requirement.

#### **INTEGRATED REFERRAL CONDITIONS:**

## 59. Asset Protection Zone

The intent of measures is to provide sufficient space and maintain reduced fuel loads so as to ensure radiant heat levels of buildings are below critical limits and to prevent direct flame contact with a building.

**Reason:** To conform to Rural Fire Service requirements.

#### 60. Asset Protection Zone

At the commencement of building works and in perpetuity the entire property shall be managed as an inner protection area as outlined within Planning for Bush Fire Protection 2006 and the Service's document 'Standards for asset protection zones'.

**Reason:** To conform to Rural Fire Service requirements.

# 61. Landscaping

Landscaping to the site is to comply with the principles of Appendix 6 of Planning for Bush Fire Protection 2006.

**Reason:** To conform to Rural Fire Service requirements.

# 62. Waste / Recycling / Green Waste Bin location

Waste / Recycling / Green Waste bins are only permitted to be presented to the street frontage the night before the collection service is due.

**Reason:** To ensure adequate waste management.

#### 63. Waste / Recycling / Green Waste Bin storage

Waste / Recycling / Green Waste bins are not permitted to be stored permanently upon the nature strip and are to be returned to within the confines of each respective property within 24 hours of the collection service being completed.

**Reason:** To ensure adequate waste management.

#### **CARRIED UNANIMOUSLY**

# PP22 30 Stanley Street, St Ives - Demolition of 2 Dwelling Houses & Construction of a Residential Flat Building comprising a total of 34 Units & Basement Car Parking for 53 Vehicles

File: DA0952/07

Ward: St Ives

Applicant: De La Vega Architects Pty Ltd Owners: Mr J F Lincoln & Mr P J S Lincoln

#### The following members of the public addressed the Panel:

P Lincoln A De La Vega To determine Development Application No.0952/07 for demolition of 2 dwelling houses and construction of a residential flat building, comprising a total of 34 units and basement car parking for 53 vehicles.

#### Resolved:

(Moved: Kerry Bedford/Vince Berkhout)

Pursuant to Section 80(1) of the Environmental Planning and Assessment Act, 1979

That Development Application No. 952/07 for demolition of 2 dwelling houses and construction of a residential flat building comprising a total of 34 units and basement car parking for 53 vehicles on land at 30 to 32 Stanley Street, St Ives, be approved for a period of two (2) years from the date of the Notice of Determination, subject to the following conditions:

# **CONDITIONS THAT IDENTIFY APPROVED PLANS:**

# 1. Approved architectural plans and documentation (new development)

The development must be carried out in accordance with work shown in colour on the following plans and documentation listed below and endorsed with Council's stamp, except where amended by other conditions of this consent:

Dwg No	Rev	Description	Drawn by	Dated	Lodged
DA-002	Α	Site Plan	de la vega architects	Oct 2007	11 March 2008
DA-003	-	Plan – Basement 2	de la vega architects	Jan 2008	11 March 2008
DA-004	-	Plan – Basement 1	de la vega architects	Jan 2008	11 March 2008
DA-005	-	Plan – Level 1	de la vega architects	Jan 2008	11 March 2008
DA-006	-	Plan – Level 2, 3 & 4	de la vega architects	Jan 2008	15 April 2008
DA-007	-	Plan – Level 5	de la vega architects	Jan 2008	11 March 2008
DA-008	-	Roof Plan	de la vega architects	Jan 2008	11 March 2008
DA-009	-	Elevations north & south	de la vega architects	Jan 2008	11 March 2008
DA-010	-	Elevations east & west	de la vega architects	Jan 2008	11 March 2008
DA-011	-	Sections	de la vega architects	Jan 2008	11 March 2008
LSK-03	G	Landscape Plan	Context Landscape Design	29 Aug 07	6 Sept 2007

**Reason:** To ensure that the development is in accordance with the determination.

# 2. Inconsistency between documents

In the event of any inconsistency between conditions of this consent and the drawings/documents referred to above, the conditions of this consent prevail.

**Reason:** To ensure that the development is in accordance with the determination.

# CONDITIONS TO BE SATISFIED PRIOR TO DEMOLITION, EXCAVATION OR CONSTRUCTION:

#### 3. Deleted duplicated condition

# 4. Notice of commencement

At least 48 hours prior to the commencement of any development (including excavation, shoring or underpinning works), a notice of commencement of

building or subdivision work form and appointment of the principal certifying authority form shall be submitted to Council.

**Reason:** Statutory requirement.

#### 5. Notification of builder's details

Prior to the commencement of any development or excavation works, the Principal Certifying Authority shall be notified in writing of the name and contractor licence number of the owner/builder intending to carry out the approved works.

**Reason:** Statutory requirement.

#### 6. Dilapidation survey and report (public infrastructure)

Prior to the commencement of any development or excavation works on site, the Principal Certifying Authority shall be satisfied that a dilapidation report on the visible and structural condition of all structures of the following public infrastructure, has been completed and submitted to Council:

#### **Public infrastructure**

- Full road pavement width, including kerb and gutter, of Stanley Street over the site frontage.
- All driveway crossings and laybacks opposite the subject site.

The report must be completed by a consulting structural/civil engineer. Particular attention must be paid to accurately recording (both written and photographic) existing damaged areas on the aforementioned infrastructure so that Council is fully informed when assessing any damage to public infrastructure caused as a result of the development.

The developer may be held liable to any recent damage to public infrastructure in the vicinity of the site, where such damage is not accurately recorded by the requirements of this condition prior to the commencement of works.

**Note:** A written acknowledgment from Council must be obtained (attesting

to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any

excavation works.

**Reason:** To record the structural condition of public infrastructure before

works commence.

# 7. Archival recording of buildings

Prior to the commencement of any development or excavation works on site, the Principal Certifying Authority shall be satisfied that an archival report has been submitted to Council's Heritage Advisor.

The report must consist of an archival standard photographic record of the building (internally and externally), its garden and views of it from the street

illustrating its relationship to neighbouring properties and the streetscape. Recording shall be undertaken in accordance with the guidelines for "Photographic Recording of Heritage Items Using Film or Digital Capture (2006)" prepared by the New South Wales Heritage Office.

Information shall be bound in an A4 report format. It shall include copies of photographs, referenced to plans of the site. Two (2) copies (one (1) copy to include negatives or CD of images shall be submitted to Council's Heritage Advisor. The recording document will be held in the local studies collection of Ku-ring-gai Library, the local historical society and Council's files.

Note:

A written acknowledgment from Council must be obtained (attesting to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any works.

Reason:

To ensure the proper management of historical artefacts and to ensure their preservation.

#### 8. Dilapidation survey and report (private property)

Prior to the commencement of any demolition or excavation works on site, the Principal Certifying Authority shall be satisfied that a dilapidation report on the visible and structural condition of all structures upon the following lands, has been completed and submitted to Council:

#### **Address**

- Units 4 and 5 of 24 Stanley Street
- The garage and shed at 36 Stanley Street
- Structures at 17 Newhaven Place.

The dilapidation report must include a photographic survey of adjoining properties detailing their physical condition, both internally and externally, including such items as walls ceilings, roof and structural members. The report must be completed by a consulting structural/geotechnical engineer as determined necessary by that professional based on the excavations for the proposal and the recommendations of the submitted geotechnical report.

In the event that access for undertaking the dilapidation survey is denied by a property owner, the applicant must demonstrate in writing to the satisfaction of the Principal Certifying Authority that all reasonable steps have been taken to obtain access and advise the affected property owner of the reason for the survey and that these steps have failed.

Note:

A copy of the dilapidation report is to be provided to Council prior to any excavation works been undertaken. The dilapidation report is for record keeping purposes only and may be used by an applicant or affected property owner to assist in any civil action required to resolve any dispute over damage to adjoining properties arising from works.

**Reason:** To record the structural condition of likely affected properties

before works commence.

#### 9. Geotechnical report

Prior to the commencement of any bulk excavation works on site, the applicant shall submit to the Principal Certifying Authority, the results of the detailed geotechnical investigation comprising a minimum of three cored boreholes to at least 1 metre below the proposed basement level. The report is to address such matters as:

- appropriate excavation methods and techniques
- vibration management and monitoring
- dilapidation survey
- support and retention of excavated faces
- hydrogeological considerations

The recommendations of the report are to be implemented during the course of the works.

**Reason:** To ensure the safety and protection of property.

#### 10. Construction and traffic management plan

Prior to the commencement of any works on site, the applicant must submit for review by Council's engineers a construction and traffic management plan. The following matters must be specifically addressed in the plan:

# 1. A plan view of the entire site and frontage roadways indicating:

- dedicated construction site entrances and exits, controlled by a certified traffic controller, to safely manage pedestrians and construction related vehicles in the frontage roadways
- turning areas within the site for construction and spoil removal vehicles, allowing a forward egress for all construction vehicles on the site
- the locations of proposed work zones in the frontage roadways
- location of any proposed crane and concrete pump and truck standing areas on and off the site
- a dedicated unloading and loading point within the site for all construction vehicles, plant and deliveries
- material, plant and spoil bin storage areas within the site, where all materials are to be dropped off and collected
- an on-site parking area for employees, tradespersons and construction vehicles as far as possible

# 2. Traffic control plan(s) for the site

All traffic control plans must be in accordance with the RTA publication "Traffic Control Worksite Manual" and prepared by a suitably qualified person (minimum 'red card' qualification). The main stages of the development requiring specific construction management measures are to be identified and specific traffic control measures identified for each

stage.

Approval is to be obtained from Council for any temporary road closures or crane use from public property. Applications to Council shall be made a minimum of 4 weeks prior to the activity proposed being undertaken.

# A detailed description and route map of the proposed route for vehicles involved in spoil removal, material delivery and machine floatage must be provided.

Light traffic roads and those subject to a load or height limit must be avoided where alternate routes exist.

A copy of this route is to be made available to all contractors and shall be clearly depicted at a location within the site.

The plan must provide evidence of RTA concurrence where construction access is provided directly from or within 20m of an arterial road.

The plan must provide a schedule of site inductions to be held on regular occasions and as determined necessary to ensure all new employees are aware of their construction management obligations. These must specify that construction-related vehicles are to comply with the approved requirements.

The plan must provide measures for minimising construction related traffic movements during school peak periods.

For those construction personnel that drive to the site, the applicant shall attempt to provide on-site parking so that their personnel's vehicles do not impact on the current parking demand in the area.

The construction and traffic management plan shall be prepared by a suitably qualified and experienced traffic consultant and be certified by this person as being in accordance with the requirements of the abovementioned documents and the requirements of this condition. The construction management measures contained in the approved plan shall be implemented in accordance with the plan prior to the commencement of, and during, works on-site including excavation.

As the plan has a direct impact on the local road network, the plan shall be submitted to and reviewed by Council's Development Engineer. Written acknowledgment from Council's Engineer shall be obtained (attesting to this condition being appropriately satisfied) and submitted to the Principal Certifying Authority prior to the commencement of any works on site.

#### Reason:

To ensure that appropriate measures have been considered during all phases of the construction process in a manner that maintains the environmental amenity and ensures the ongoing safety and protection of people.

#### 11. Work zone

If a works zone is proposed, the applicant must make a written application to the Ku-ring-gai Local Traffic Committee to install the work zone. Work zones are provided specifically for the set down and pick up of materials and not for the parking of private vehicles associated with the site. Work zones will generally not be approved where there is sufficient space on-site for the setting down and picking up of goods being taken to or from a construction site.

If the work zone is approved by the Local Traffic Committee, the applicant must obtain a written copy of the related resolution from the Ku-ring-gai Local Traffic Committee and submit this to the Principal Certifying Authority prior to commencement of any works on site.

Where approval of the work zone is resolved by the Committee, the necessary work zone signage shall be installed (at the cost of the applicant) and the adopted fee paid prior to commencement of any works on site. At the expiration of the work zone approval, the applicant is required to remove the work zone signs and reinstate any previous signs at their expense.

In the event the work zone is required for a period beyond that initially approved by the Traffic Committee, the applicant shall make a payment to Council for the extended period in accordance with Council's schedule of fees and charges for work zones prior to the extended period commencing.

**Reason:** To ensure that appropriate measures have been made for the operation of the site during the construction phase.

# 12. Temporary construction exit

A temporary construction exit, together with necessary associated temporary fencing, shall be provided prior to commencement of any work on the site and shall be maintained throughout the duration and progress of construction.

**Reason:** To reduce or eliminate the transport of sediment from the construction site onto public roads.

#### 13. Sediment controls

Prior to any work commencing on site, sediment and erosion control measures shall be installed along the contour immediately downslope of any future disturbed areas.

The form of the sediment controls to be installed on the site shall be determined by reference to the 'NSW Department of Housing manual 'Managing Urban Stormwater: Soils and Construction'. The erosion controls shall be maintained in an operational condition until the development activities have been completed and the site fully stabilised. Sediment shall be removed from the sediment controls following each heavy or prolonged rainfall period.

**Reason:** To preserve and enhance the natural environment.

#### 14. Erosion and drainage management

Earthworks and/or demolition of any existing buildings shall not commence until an erosion and sediment control plan is submitted to and approved by the Principal Certifying Authority. The plan shall comply with the guidelines set out in the NSW Department of Housing manual "Managing Urban Stormwater: Soils and Construction" certificate. Erosion and sediment control works shall be implemented in accordance with the erosion and sediment control plan.

**Reason:** To preserve and enhance the natural environment.

# 15. Tree protection fencing

To preserve the following tree/s, no work shall commence until the area beneath their canopy is fenced off at the specified radius from the trunk/s to prevent any activities, storage or the disposal of materials within the fenced area. The fence/s shall be maintained intact until the completion of all demolition/building work on site.

Schedule	
No/Tree/location	Radius in metres
5/ <i>Juniperus sp.</i> (Juniper)	3 metres
Adjacent to the site's central rear boundary.	
6/ <i>Juniperus sp.</i> (Juniper)	3 metres
Adjacent to the site's central rear boundary.	
22/ <i>Jacaranda mimosifolia</i> (Jacaranda)	5 metres
Adjacent to the site's central Stanley Street boundary.	
35/ <i>Camellia sasanqua</i> (Chinese Camellia)	4 metres
Adjacent to the site's northeastern corner.	
Row of <i>Camellia japonica</i> (Japanese Camellia)	2 metres
Site's western boundary.	

**Reason:** To protect existing trees during the construction phase.

# 16. Tree protection fencing excluding structure

To preserve the following tree/s, no work shall commence until the area beneath their canopy excluding that area of the proposed BUILDING, FEATURE WALLS and PATHS shall be fenced off for the specified radius from the trunk to prevent any activities, storage or the disposal of materials within the fenced area. The fence/s shall be maintained intact until the completion of all demolition/building work on site:

Schedule No/Tree/location	Radius in metres
16/Araucaria cunninghamii (Hoop Pine)	7 metres
Close to the site's south-eastern corner.	
18/ <i>Liquidambar styraciflua</i> (Liquidambar)	7 metres
Close to the eastern end of the site's Stanley Street	
boundary.	
19/ <i>Franklinia axillaris</i> (Gordonia)	4 metres
Adjacent to the site's central Stanley Street boundary.	

Schedule	
No/Tree/location	Radius in metres
20/ <i>Hymenosporum flavum</i> (Native Frangipani)	3 metres
Adjacent to the site's central Stanley Street boundary.	
21/ <i>Cedrus deodara</i> (Himalayan Cedar)	5 metres
Adjacent to the site's central Stanley Street boundary.	
23/ <i>Magnolia x soulangiana</i> (Magnolia)	4 metres
Adjacent to the site's central Stanley Street boundary.	
24/ <i>Magnolia x soulangiana</i> (Magnolia)	4 metres
Adjacent to the site's central Stanley Street boundary.	
25/ <i>Rhododendron sp.</i> (Broad leaf Rhododendron)	3 metres
Adjacent to and near the western end of the site's Stanley	
Street boundary.	

**Reason:** To protect existing trees during the construction phase.

# 17. Tree Protective Fencing Type Galvanised Mesh

The tree protection fencing shall be constructed of galvanised pipe at 2.4 metre spacings and connected by securely attached chain mesh fencing to a minimum of 1.8 metres in height prior to work commencing.

**Reason:** To protect existing trees during construction phase.

# 18. Tree protection signage

Cabadula

Prior to works commencing, tree protection signage is to be attached to each tree protection zone, displayed in a prominent position and the sign repeated at 10 metres intervals or closer where the fence changes direction. Each sign shall contain in a clearly legible form, the following information:

- tree protection zone
- this fence has been installed to prevent damage to the trees and their growing environment both above and below ground and access is restricted
- any encroachment not previously approved within the tree protection zone shall be the subject of an arborist's report
- the arborist's report shall provide proof that no other alternative is available
- the arborist's report shall be submitted to the Principal Certifying Authority for further consultation with Council
- the name, address, and telephone number of the developer.

**Reason:** To protect existing trees during the construction phase.

#### 19. Tree protection mulching

Prior to works commencing and throughout construction, the area of the tree protection zone is to be mulched to a depth of 100mm with composted organic material being 75% Eucalyptus leaf litter and 25% wood.

**Reason:** To protect existing trees during the construction phase.

#### 20. Tree fencing inspection

Upon installation of the required tree protection measures, an inspection of the site by the Principal Certifying Authority is required to verify that tree protection measures comply with all relevant conditions.

**Reason:** To protect existing trees during the construction phase.

#### 21. Construction waste management plan

Prior to the commencement of any works, the Principal Certifying Authority shall be satisfied that a waste management plan, prepared by a suitably qualified person, has been prepared in accordance with Council's DCP 40 – Construction and Demolition Waste Management.

The plan shall address all issues identified in DCP 40, including but not limited to: the estimated volume of waste and method for disposal for the construction and operation phases of the development.

**Note:** The plan shall be provided to the Certifying Authority.

**Reason:** To ensure appropriate management of construction waste.

# 22. Noise and vibration management plan

Prior to the commencement of any works, a noise and vibration management plan is to be prepared by a suitably qualified expert addressing the likely noise and vibration from demolition, excavation and construction of the proposed development and provided to the Principal Certifying Authority. The management plan is to identify amelioration measures to ensure the noise and vibration levels will be compliant with the relevant Australian Standards and Ku-ring-gai Council's Code for the Control and Regulation of Noise on Building Sites. The report shall be prepared in consultation with any geotechnical report that itemises equipment to be used for excavation works.

The management plan shall address, but not be limited to, the following matters

- identification of the specific activities that will be carried out and associated noise sources
- identification of all potentially affected sensitive receivers, including residences, churches, commercial premises, schools and properties containing noise sensitive equipment
- the construction noise objective specified in the conditions of this consent
- the construction vibration criteria specified in the conditions of this consent
- determination of appropriate noise and vibration objectives for each identified sensitive receiver
- noise and vibration monitoring, reporting and response procedures
- assessment of potential noise and vibration from the proposed demolition, excavation and construction activities, including noise from

- construction vehicles and any traffic diversions
- description of specific mitigation treatments, management methods and procedures that will be implemented to control noise and vibration during construction
- construction timetabling to minimise noise impacts including time and duration restrictions, respite periods and frequency
- construction timetabling to minimise noise impacts including time and duration restrictions, respite periods and frequency
- procedures for notifying residents of construction activities that are likely to affect their amenity through noise and vibration
- contingency plans to be implemented in the event of non-compliances and/or noise complaints
- compliance with Council's Code for the Control and Regulation of Noise on Building Sites

**Reason:** To protect the amenity afforded to surrounding residents during the construction process.

# 23. CCTV report of existing Council pipe system near works

Prior to the commencement of any works on site, qualified practitioners must undertake a closed circuit television inspection and then report on the existing condition of the Council drainage pipeline traversing the subject property. The report must be provided to Council's, Development Engineer and is to include a copy of the video footage of the pipeline. A written acknowledgment from Council's Development Engineer (attesting to this condition being appropriately satisfied) shall be obtained and submitted to the Principal Certifying Authority prior to the commencement of any works on site.

**Reason:** To protect Council's infrastructure.

# CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF THE CONSTRUCTION CERTIFICATE:

#### 24. Amendments to approved landscape plan

Prior to the issue of a Construction Certificate, the Principal Certifying Authority shall be satisfied that the approved landscape plans, listed below and endorsed with Council's stamp, have been amended in accordance with the requirements of this condition as well as other conditions of this consent:

Plan no.	Drawn by	Dated
LSK-03 Rev. G for Project No.	Context Landscape	29.08.07
04.558	Design	

The above landscape plan(s) shall be amended in the following ways:

All structures shall be consistent with the approved Architectural plans.

Prior to the issue of the Construction Certificate, the Principal Certifying Authority shall be satisfied that the landscape plan has been amended as required by this condition.

**Note:** An amended landscape plan, prepared by a landscape architect or

qualified landscape designer shall be submitted to the Certifying

Authority.

**Reason:** To ensure that the development is in accordance with the

determination.

# 25. Long service levy

In accordance with Section 109F(i) of the Environmental Planning and Assessment Act a Construction Certificate shall not be issued until any long service levy payable under Section 34 of the Building and Construction Industry Long Service Payments Act 1986 (or where such levy is payable by instalments, the first instalment of the levy) has been paid. Council is authorised to accept payment. Where payment has been made elsewhere, proof of payment is to be provided to Council.

**Reason:** Statutory requirement.

#### 26. Builder's indemnity insurance

The applicant, builder, developer or person who does the work on this development, must arrange builder's indemnity insurance and submit the certificate of insurance in accordance with the requirements of Part 6 of the Home Building Act 1989 to the Certifying Authority for endorsement of the plans accompanying the Construction Certificate.

It is the responsibility of the applicant, builder or developer to arrange the builder's indemnity insurance for residential building work over the value of \$12,000. The builder's indemnity insurance does not apply to commercial or industrial building work or to residential work valued at less than \$12,000, nor to work undertaken by persons holding an owner/builder's permit issued by the Department of Fair Trading (unless the owner/builder's property is sold within 7 years of the commencement of the work).

**Reason:** Statutory requirement.

# 27. External finishes and materials (new building)

Prior to the issue of the Construction Certificate, the Certifying Authority shall be satisfied that the external finishes of the building are consistent with the character of the streetscape. The materials are to be complimentary to the approved architectural appearance of the development. Nothing in this condition is to be construed as permitting the replacement of previously submitted materials with inferior or inadequate materials or finishes.

**Note:** Details of the colour, finish and substance of all external materials,

including schedules and a sample board of materials and colours,

are to be submitted.

**Reason:** To protect the streetscape and the integrity of the approved

development.

# 28. Outdoor lighting

Prior to the issue of a Construction Certificate, the Certifying Authority shall be satisfied that all outdoor lighting will comply with AS/NZ1158.3: 1999 Pedestrian Area (Category P) Lighting and AS4282: 1997 Control of the Obtrusive Effects of Outdoor Lighting.

**Note:** Details demonstrating compliance with these requirements are to

be submitted prior to the issue of a Construction Certificate.

Reason: To provide high quality external lighting for security without adverse

affects on public amenity from excessive illumination levels.

# 29. Air drying facilities

Prior to the issue of the Construction Certificate, the Certifying Authority shall be satisfied that a common open space area dedicated for open air drying of clothes is provided. This area is to be located at ground level behind the building line and in a position not visible from the public domain.

In lieu of the above, written confirmation that all units will be provided with internal clothes drying facilities prior to the Occupation Certificate is to be submitted to the Certifying Authority prior to the issue of the Construction Certificate.

**Reason:** Amenity & energy efficiency.

#### 30. Access for people with disabilities (residential)

Prior to the issue of the Construction Certificate, the Certifying Authority shall be satisfied that access for people with disabilities to and from and between the public domain, residential units and all common open space areas is provided. Consideration must be given to the means of dignified and equitable access.

Compliant access provisions for people with disabilities shall be clearly shown on the plans submitted with the Construction Certificate. All details shall be provided to the Principal Certifying Authority prior to the issue of the Construction Certificate. All details shall be prepared in consideration of the Disability Discrimination Act, and the relevant provisions of AS1428.1, AS1428.2, AS1428.4 and AS 1735.12.

**Reason:** To ensure the provision of equitable and dignified access for all

people in accordance with disability discrimination legislation and

relevant Australian Standards.

#### 31. Adaptable units

Prior to the issue of the Construction Certificate, the Certifying Authority shall be satisfied that the nominated adaptable units within the development application, 1.03, 2.03, 3.03 & 4.03, are designed as adaptable housing in

accordance with the provisions of Australian Standard AS4299-1995: Adaptable Housing.

**Note:** Evidence from an appropriately qualified professional

demonstrating compliance with this control is to be submitted to and approved by the Certifying Authority prior to the issue of the

Construction Certificate.

Reason: Disabled access & amenity.

# 32. Stormwater management plan

Prior to issue of the Construction Certificate, the applicant must submit, for approval by the Principal Certifying Authority, scale construction plans and specifications in relation to the stormwater management and disposal system for the development. The plan(s) must include the following detail:

- exact location and reduced level of discharge point to the public drainage system
- Layout of the property drainage system components, including but not limited to (as required) gutters, downpipes, spreaders, pits, swales, kerbs, cut-off and intercepting drainage structures, subsoil drainage, flushing facilities and all ancillary stormwater plumbing all designed for a 235mm/hour rainfall intensity for a duration of five (5) minutes (1:50 year storm recurrence)
- location(s), dimensions and specifications for the required rainwater storage and reuse tanks and systems and where proprietary products are to be used, manufacturer specifications or equivalent shall be provided
- specifications for reticulated pumping facilities (including pump type and manufacturer specifications) and ancillary plumbing to fully utilise rainwater in accordance with Ku-ring-gai Council Development Control Plan 47 and/or BASIX commitments
- details of the required on-site detention tanks required by Ku-ring-gai Water Management DCP 47, including dimensions, materials, locations, orifice and discharge control pit details as required (refer Chapter 6 and Appendices 2, 3 and 5 of DCP 47 for volume, PSD and design requirements)
- the required basement stormwater pump-out system is to cater for driveway runoff and subsoil drainage (refer appendix 7.1.1 of Development Control Plan 47 for design)

The above construction drawings and specifications are to be prepared by a qualified and experienced civil/hydraulic engineer in accordance with Council's Water Management Development Control Plan 47, Australian Standards 3500.2 and 3500.3 - Plumbing and Drainage Code and the Building Code of Australia. The plans may be generally based on the Stormwater management plans by Warren Smith & Partners submitted with the development application, which are to be advanced as necessary for construction certificate issue purposes.

**Reason:** To protect the environment.

#### 33. Stormwater retention

Prior to the issue of a Construction Certificate, the Principal Certifying Authority is to be satisfied that:

- 1. A mandatory rainwater retention and re-use system, comprising storage tanks and ancillary plumbing is provided. The minimum total storage volume of the rainwater tank system, and the prescribed re-use of the water on site must satisfy all relevant BASIX commitments and the requirements specified in Chapter 6 of Ku-ring-gai Water Management Development Control Plan 47; and
- 2. An on-site stormwater detention system must be provided to control the rate of runoff leaving the site. The minimum volume of the required on-site detention system must be determined in accordance with Chapter 6 of the Ku-ring-gai Council Water Management Development Control Plan 47 having regard to the specified volume concession offered in lieu of installing rainwater retention tanks. The on-site detention system must be designed by a qualified civil/hydraulic engineer and must satisfy the design controls set out in Appendix 5 of DCP 47.

**Reason:** To protect the environment.

#### 34. Excavation for services

Prior to the issue of the Construction Certificate, the Principal Certifying shall be satisfied that no proposed underground services (ie. water, sewerage, drainage, gas or other service) unless previously approved by conditions of consent, are located beneath the canopy of any tree protected under Council's Tree Preservation Order, located on the subject allotment and adjoining allotments.

**Note:** A plan detailing the routes of these services and trees protected

under the Tree Preservation Order, shall be submitted to the

Principal Certifying Authority.

**Reason:** To ensure the protection of trees.

#### 35. Landscape plan

Prior to the issue of the Construction Certificate, the Principal Certifying Authority shall be satisfied that a landscape plan has been completed in accordance with Council's DA Guide, relevant development control plans and the conditions of consent by a landscape architect or qualified landscape designer.

**Note:** The landscape plan must be submitted to the Principal Certifying

Authority.

**Reason:** To ensure adequate landscaping of the site.

#### 36. Location of plant (residential flat buildings)

Prior to the issue of the Construction Certificate, the Certifying Authority shall be satisfied that all plant and equipment (including but not limited to air conditioning equipment) is located within the basement or the designated plants rooms located on Level 5. All plant equipment, including ducting, must be contained wholly within the building.

**C1. Note:** Architectural plans identifying the location of all plant and equipment shall be provided to the Certifying Authority.

**Reason:** To minimise impact on surrounding properties, improved visual

appearance and amenity for locality.

#### 37. Driveway crossing levels

Prior to issue of the Construction Certificate, driveway and associated footpath levels for any new, reconstructed or extended sections of driveway crossings between the property boundary and road alignment must be obtained from Kuring-gai Council. Such levels are only able to be issued by Council under the Roads Act 1993. All footpath crossings, laybacks and driveways are to be constructed according to Council's specifications "Construction of Gutter Crossings and Footpath Crossings".

Specifications are issued with alignment levels after completing the necessary application form at Customer Services and payment of the assessment fee. When completing the request for driveway levels application from Council, the applicant must attach a copy of the relevant development application drawing which indicates the position and proposed level of the proposed driveway at the boundary alignment.

This development consent is for works wholly within the property. Development consent does not imply approval of footpath or driveway levels, materials or location within the road reserve, regardless of whether this information is shown on the development application plans. The grading of such footpaths or driveways outside the property shall comply with Council's standard requirements. The suitability of the grade of such paths or driveways inside the property is the sole responsibility of the applicant and the required alignment levels fixed by Council may impact upon these levels.

The construction of footpaths and driveways outside the property in materials other than those approved by Council is not permitted.

**Reason:** To provide suitable vehicular access without disruption to

pedestrian and vehicular traffic.

#### 38. Driveway grades – basement car parks

Prior to the issue of the Construction Certificate, longitudinal driveway sections are to be prepared by a qualified civil/traffic engineer and be submitted for to and approved by the Certifying Authority. These profiles are to be at 1:100 scale along both edges of the proposed driveway, starting from the centreline of the

frontage street carriageway to the proposed basement floor level. The traffic engineer shall provide specific written certification on the plans that:

- vehicular access can be obtained using grades of 20% (1 in 5) maximum and
- all changes in grade (transitions) comply with Australian Standard 2890.1
   "Off-street car parking" (refer clause 2.5.3) to prevent the scraping of the underside of vehicles.

If a new driveway crossing is proposed, the longitudinal sections must incorporate the driveway crossing levels as issued by Council upon prior application.

**Reason:** To provide suitable vehicular access without disruption to pedestrian and vehicular traffic.

#### 39. Basement car parking details

Prior to issue of the Construction Certificate, certified parking layout plan(s) to scale showing all aspects of the vehicle access and accommodation arrangements must be submitted to and approved by the Certifying Authority. A qualified civil/traffic engineer must review the proposed vehicle access and accommodation layout and provide written certification on the plans that:

- all parking space dimensions, driveway and aisle widths, driveway grades, transitions, circulation ramps, blind aisle situations and other trafficked areas comply with Australian Standard 2890.1 – 2004 "Off-street car parking"
- a clear height clearance of 2.5 metres (required under DCP40 for waste collection trucks) is provided over the designated garbage collection truck manoeuvring areas within the basement
- no doors or gates are provided in the access driveways to the basement car park which would prevent unrestricted access for internal garbage collection at any time from the basement garbage storage and collection area
- the vehicle access and accommodation arrangements are to be constructed and marked in accordance with the certified plans

**Reason:** To ensure that parking spaces are in accordance with the approved development.

#### 40. Car parking allocation

Car parking within the development shall be allocated in the following way:

Resident car spaces 44
Visitor spaces 9
Total spaces 53

Each adaptable dwelling must be provided with car parking complying with the dimensional and location requirements of AS2890.1 – parking spaces for people with disabilities.

At least one visitor space shall also comply with the dimensional and location requirements of AS2890.1 – parking spaces for people with disabilities.

Consideration must be given to the means of access from disabled car parking spaces to other areas within the building and to footpath and roads and shall be clearly shown on the plans submitted with the Construction Certificate.

At least one visitor parking bay shall be provided with a tap for car washing.

**Reason:** To ensure equity of access and appropriate facilities are available for people with disabilities in accordance with federal legislation.

## 41. Number of bicycle spaces

The basement car park shall be adapted to provide 10 bicycle spaces in accordance with Part 5.1 of DCP 55. The bicycle parking spaces shall be designed in accordance with AS2890.3. Details shall be submitted to the satisfaction of the Certifying Authority prior to the issue of a Construction Certificate.

**Reason:** To provide alternative modes of transport to and from the site.

# 42. Energy Australia requirements

Prior to issue of the Construction Certificate, the applicant must contact Energy Australia regarding power supply for the subject development. A written response detailing the full requirements of Energy Australia (including any need for underground cabling, substations or similar within or in the vicinity the development) shall be submitted to the Principal Certifying Authority for approval prior to issue of the Construction Certificate.

Any structures or other requirements of Energy Australia shall be indicated on the plans issued with the Construction Certificate, to the satisfaction of the Principal Certifying Authority and Energy Australia. The requirements of Energy Australia must be met in full prior to issue of the Occupation Certificate.

**Reason:** To ensure compliance with the requirements of Energy Australia.

#### 43. Utility provider requirements

Prior to issue of the Construction Certificate, the applicant must make contact with all relevant utility providers whose services will be impacted upon by the development. A written copy of the requirements of each provider, as determined necessary by the Certifying Authority, must be obtained. All utility services or appropriate conduits for the same must be provided by the developer in accordance with the specifications of the utility providers.

**Reason:** To ensure compliance with the requirements of relevant utility providers.

#### 44. Underground services

All electrical services (existing and proposed) shall be undergrounded from the proposed building on the site to the appropriate power pole(s) or other connection point. Undergrounding of services must not disturb the root system of existing trees and shall be undertaken in accordance with the requirements of the relevant service provided. Documentary evidence that the relevant service provider has been consulted and that their requirements have been met are to be provided to the Certifying Authority prior to the issue of the Construction Certificate. All electrical and telephone services to the subject property must be placed underground and any redundant poles are to be removed at the expense of the applicant.

**Reason:** To provide infrastructure that facilitates the future improvement of the streetscape by relocation of overhead lines below ground.

CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF THE CONSTRUCTION CERTIFICATE OR PRIOR TO DEMOLITION, EXCAVATION OR CONSTRUCTION (WHICHEVER COMES FIRST):

#### 45. Infrastructure restorations fee

To ensure that damage to Council Property as a result of construction activity is rectified in a timely matter:

- a) All work or activity taken in furtherance of the development the subject of this approval must be undertaken in a manner to avoid damage to Council Property and must not jeopardise the safety of any person using or occupying the adjacent public areas.
- b) The applicant, builder, developer or any person acting in reliance on this approval shall be responsible for making good any damage to Council Property, and for the removal from Council Property of any waste bin, building materials, sediment, silt, or any other material or article.
- c) The Infrastructure Restoration Fee must be paid to the Council by the applicant prior to both the issue of the Construction Certificate and the commencement of any earthworks or construction.
- d) In consideration of payment of the Infrastructure Restorations Fee, Council will undertake such inspections of Council Property as Council considers necessary and also undertake, on behalf of the applicant, such restoration work to Council Property, if any, that Council considers necessary as a consequence of the development. The provision of such restoration work by the Council does not absolve any person of the responsibilities contained in (a) to (b) above. Restoration work to be undertaken by the Council referred to in this condition is limited to work that can be undertaken by Council at a cost of not more than the Infrastructure Restorations Fee payable pursuant to this condition.

(\$56,102.57)

#### e) In this condition:

"Council Property" includes any road, footway, footpath paving, kerbing, guttering, crossings, street furniture, seats, letter bins, trees, shrubs, lawns, mounds, bushland, and similar structures or features on any road or public road within the meaning of the Local Government Act 1993 (NSW) or any public place; and

"Infrastructure Restoration Fee" means the Infrastructure Restorations Fee calculated in accordance with the Schedule of Fees & Charges adopted by Council as at the date of payment and the cost of any inspections required by the Council of Council Property associated with this condition.

**Reason:** To maintain public infrastructure.

## 46. Section 94 contribution – residential development

A contribution pursuant to section 94 of the Environmental Planning and Assessment Act as specified in Ku-ring-gai Section 94 Contributions Plan 2004-2009 for the services detailed in column A and for the amount detailed in Column B is required.

Column A community facilities park acquisition and embellishment works sportsgrounds works aquatic / leisure centres traffic and transport section 94 Plan administration	<b>Column B</b> \$1117.76 \$6574.28 \$1318.32 \$27.82 \$150.28 \$100.04
Total contribution is:	\$9,288.50 per person
1 x small unit (under 75m2) @ \$11,796.40 31 x medium units (75-110m2) @ \$16,533.54 2 x very large units (>150m2) @ \$32,324.00	\$11,796.40 \$512,539.74 \$64,648.00

SUB TOTAL \$588,984.14

Less credit for existing dwellings
1 x large dwelling (111-150m2) @ \$23,778.57 (\$23,778.57)
1 x very large dwelling (>150m2) @ \$32,324.00 (\$32,324.00)

TOTAL PAYABLE \$532,881.57

The contribution shall be paid to Council prior to the commencement of any development (including demolition) or prior to the issue of the Construction Certificate (whichever comes first). The charges may vary at the time of payment in accordance with Council's Section 94 Contributions Plan to reflect changes in land values, construction costs and the consumer price index. Prior to payment, you are advised to check the contribution amount required with Council.

**Reason:** To ensure the provision, extension or augmentation of community

facilities, recreation facilities, open space and administration that will, or are likely to be, required as a consequence of the

development.

# CONDITIONS TO BE SATISFIED DURING THE DEMOLITION, EXCAVATION AND **CONSTRUCTION PHASES:**

### 47. Approved plans to be on site

A copy of all approved and certified plans, specifications and documents incorporating conditions of consent and certification (including the Construction Certificate if required for the work) shall be kept on site at all times during the demolition, excavation and construction phases and must be readily available to any officer of Council or the Principal Certifying Authority.

Reason: To ensure that the development is in accordance with the determination.

#### 48. **Engineering fees**

For the purpose of any development related inspections by Ku-ring-gai Council engineers, the corresponding fees set out in Councils adopted Schedule of Fees and Charges are payable to Council. A re-inspection fee per visit may be charged where work is unprepared at the requested time of inspection, or where remedial work is unsatisfactory and a further inspection is required. Engineering fees must be paid in full prior to any final consent from Council.

**Reason:** To protect public infrastructure.

#### Prescribed conditions 49.

The applicant shall comply with any relevant prescribed conditions of development consent under clause 98 of the Environmental Planning and Assessment Regulation. For the purposes of section 80A (11) of the Environmental Planning and Assessment Act, the following conditions are prescribed in relation to a development consent for development that involves any building work:

- The work must be carried out in accordance with the requirements of the Building Code of Australia
- In the case of residential building work for which the Home Building Act 1989 requires there to be a contract of insurance in force in accordance with Part 6 of that Act, that such a contract of insurance is in force before any works commence.

**Reason:** Statutory requirement.

#### 50. Statement of compliance with Australian Standards

The demolition work shall comply with the provisions of Australian Standard AS2601: 2001 The Demolition of Structures. The work plans required by AS2601: 2001 shall be accompanied by a written statement from a suitably qualified person that the proposal contained in the work plan comply with the safety requirements of the Standard. The work plan and the statement of compliance shall be submitted to the satisfaction of the Principal Certifying Authority prior to the commencement of any works.

**Reason:** To ensure compliance with the Australian Standards.

#### 51. Construction noise

During excavation, demolition and construction phases, noise generated from the site shall be controlled in accordance with the recommendations of the approved noise and vibration management plan.

**Reason:** To ensure reasonable standards of amenity to neighbouring

properties.

### 52. Site notice

A site notice shall be erected on the site prior to any work commencing and shall be displayed throughout the works period.

The site notice must:

- be prominently displayed at the boundaries of the site for the purposes of informing the public that unauthorised entry to the site is not permitted
- display project details including, but not limited to the details of the builder, Principal Certifying Authority and structural engineer
- be durable and weatherproof
- display the approved hours of work, the name of the site/project manager, the responsible managing company (if any), its address and 24 hour contact phone number for any inquiries, including construction/noise complaint are to be displayed on the site notice
- be mounted at eye level on the perimeter hoardings/fencing and is to state that unauthorised entry to the site is not permitted

**Reason:** To ensure public safety and public information.

#### 53. Dust control

During excavation, demolition and construction, adequate measures shall be taken to prevent dust from affecting the amenity of the neighbourhood. The following measures must be adopted:

- physical barriers shall be erected at right angles to the prevailing wind direction or shall be placed around or over dust sources to prevent wind or activity from generating dust
- earthworks and scheduling activities shall be managed to coincide with the next stage of development to minimise the amount of time the site is left cut or exposed
- all materials shall be stored or stockpiled at the best locations
- the ground surface should be dampened slightly to prevent dust from becoming airborne but should not be wet to the extent that run-off occurs
- all vehicles carrying spoil or rubble to or from the site shall at all times be covered to prevent the escape of dust
- all equipment wheels shall be washed before exiting the site using manual or automated sprayers and drive-through washing bays
- gates shall be closed between vehicle movements and shall be fitted with

shade cloth

cleaning of footpaths and roadways shall be carried out daily

**Reason:** To protect the environment and amenity of surrounding properties.

#### 54. Post-construction dilapidation report

The applicant shall engage a suitably qualified person to prepare a post construction dilapidation report at the completion of the construction works. This report is to ascertain whether the construction works created any structural damage to adjoining buildings, infrastructure and roads. The report is to be submitted to the Principal Certifying Authority. In ascertaining whether adverse structural damage has occurred to adjoining buildings, infrastructure and roads, the Principal Certifying Authority must:

- compare the post-construction dilapidation report with the preconstruction dilapidation report
- have written confirmation from the relevant authority that there is no adverse structural damage to their infrastructure and roads.

A copy of this report is to be forwarded to Council at the completion of the construction works.

**Reason:** Management of records.

# 55. Further geotechnical input

The geotechnical and hydro-geological works implementation, inspection, testing and monitoring program for the excavation and construction works must be in accordance with the report by Geotechnique. Over the course of the works, a qualified geotechnical/hydro-geological engineer must complete the following:

- further geotechnical investigations and testing recommended in the above report(s) and as determined necessary
- further monitoring and inspection at the hold points recommended in the above report(s) and as determined necessary
- written report(s) including certification(s) of the geotechnical inspection, testing and monitoring programs

**Reason:** To ensure the safety and protection of property.

# 56. Compliance with submitted geotechnical report

A contractor with specialist excavation experience must undertake the excavations for the development and a suitably qualified and consulting geotechnical engineer must oversee excavation.

Geotechnical aspects of the development work, namely:

- appropriate excavation method and vibration control
- support and retention of excavated faces

# hydro-geological considerations

must be undertaken in accordance with the recommendations of the geotechnical report prepared by Geotechnique. Approval must be obtained from all affected property owners, including Ku-ring-gai Council, where rock anchors (both temporary and permanent) are proposed below adjoining property(ies).

**Reason:** To ensure the safety and protection of property.

#### 57. Use of road or footpath

During excavation, demolition and construction phases, no building materials, plant or the like are to be stored on the road or footpath without written approval being obtained from Council beforehand. The pathway shall be kept in a clean, tidy and safe condition during building operations. Council reserves the right, without notice, to rectify any such breach and to charge the cost against the applicant/owner/builder, as the case may be.

**Reason:** To ensure safety and amenity of the area.

#### 58. Guarding excavations

All excavation, demolition and construction works shall be properly guarded and protected with hoardings or fencing to prevent them from being dangerous to life and property.

**Reason:** To ensure public safety.

### 59. Toilet facilities

During excavation, demolition and construction phases, toilet facilities are to be provided, on the work site, at the rate of one toilet for every 20 persons or part of 20 persons employed at the site.

**Reason:** Statutory requirement.

#### 60. Protection of public places

If the work involved in the erection, demolition or construction of the development is likely to cause pedestrian or vehicular traffic in a public place to be obstructed or rendered inconvenient, or building involves the enclosure of a public place, a hoarding or fence must be erected between the work site and the public place.

If necessary, a hoarding is to be erected, sufficient to prevent any substance from, or in connection with, the work falling into the public place.

The work site must be kept lit between sunset and sunrise if it is likely to be hazardous to persons in the public place.

Any hoarding, fence or awning is to be removed when the work has been completed.

**Reason:** To protect public places.

### 61. Construction signage

All construction signs must comply with the following requirements:

- are not to cover any mechanical ventilation inlet or outlet vent
- are not illuminated, self-illuminated or flashing at any time
- are located wholly within a property where construction is being undertaken
- refer only to the business(es) undertaking the construction and/or the site at which the construction is being undertaken
- are restricted to one such sign per property
- do not exceed 2.5m<sup>2</sup>
- are removed within 14 days of the completion of all construction works

**Reason:** To ensure compliance with Council's controls regarding signage.

## 62. Approval for rock anchors

Approval is to be obtained from the property owner for any anchors proposed beneath adjoining private property. If such approval cannot be obtained, then the excavated faces are to be shored or propped in accordance with the recommendations of the geotechnical and structural engineers.

**Reason:** To ensure the ongoing safety and protection of property.

#### 63. Road reserve safety

All public footways and roadways fronting and adjacent to the site must be maintained in a safe condition at all times during the course of the development works. Construction materials must not be stored in the road reserve. A safe pedestrian circulation route and a pavement/route free of trip hazards must be maintained at all times on or adjacent to any public access ways fronting the construction site. Where public infrastructure is damaged, repair works must be carried out when and as directed by Council officers. Where pedestrian circulation is diverted on to the roadway or verge areas, clear directional signage and protective barricades must be installed in accordance with AS1742-3 (1996) "Traffic Control Devices for Work on Roads". If pedestrian circulation is not satisfactorily maintained across the site frontage, and action is not taken promptly to rectify the defects, Council may undertake proceedings to stop work.

**Reason:** To ensure safe public footways and roadways during construction.

#### 64. Road repairs necessitated by excavation and construction works

It is highly likely that damage will be caused to the roadway at or near the subject site as a result of the construction (or demolition or excavation) works. The applicant, owner and builder (and demolition or excavation contractor as appropriate) will be held responsible for repair of such damage, regardless of

the Infrastructure Restorations Fee paid (this fee is to cover wear and tear on Council's wider road network due to heavy vehicle traffic, not actual major damage).

Section 102(1) of the Roads Act states "A person who causes damage to a public road is liable to pay to the appropriate roads authority the cost incurred by that authority in making good the damage."

Council will notify when road repairs are needed, and if they are not carried out within 48 hours, then Council will proceed with the repairs, and will invoice the applicant, owner and relevant contractor for the balance.

**Reason:** To protect public infrastructure.

#### 65. Services

Where required, the adjustment or inclusion of any new utility service facilities must be carried out by the applicant and in accordance with the requirements of the relevant utility authority. These works shall be at no cost to Council. It is the applicants full responsibility to make contact with the relevant utility authorities to ascertain the impacts of the proposal upon utility services (including water, phone, gas and the like). Council accepts no responsibility for any matter arising from its approval to this application involving any influence upon utility services provided by another authority.

**Reason:** Provision of utility services.

#### 66. Temporary rock anchors

If the use of temporary rock anchors extending into the road reserve is proposed, then approval must be obtained from Council and/or the Roads and Traffic Authority in accordance with Section 138 of the Roads Act 1993. The Applicant is to submit details of all the work that is to be considered, and the works are not to commence until approval has been granted. The designs are to include details of the following:

- How the temporary rock anchors will be left in a way that they will not harm or interfere with any future excavation in the public road
- That the locations of the rock anchors are registered with Dial Before You
   Dig
- That approval of all utility authorities likely to use the public road has been obtained. All temporary rock anchors are located outside the allocations for the various utilities as adopted by the Streets Opening Conference.
- That any remaining de-stressed rock anchors are sufficiently isolated from the structure that they cannot damage the structure if pulled during future excavations or work in the public road.
- That signs will be placed and maintained on the building stating that destressed rock anchors remain in the public road and include a contact number for the building manager. The signs are to be at least 600mm x 450mm with lettering on the signs is to be no less than 75mm high. The signs are to be at not more than 60m spacing. At least one sign must be

visible from all locations on the footpath outside the property. The wording on the signs is to be submitted to Council's Director Technical Services for approval before any signs are installed.

Permanent rock anchors are not to be used where any part of the anchor extends outside the development site into public areas or road reserves.

All works in the public road are to be carried out in accordance with the Conditions of Construction issued with any approval of works granted under Section 138 of the Roads Act 1993.

**Reason:** To ensure the ongoing safety and protection of property.

## 67. Structures to be clear of drainage easements

During all phases of demolition, excavation and construction, it is the full responsibility of the applicant and their contractors to:

- ascertain the exact location of the Council drainage pipe traversing the site in the vicinity of the works
- take full measures to protect the in-ground Council drainage system
- ensure dedicated overland flow paths are satisfactorily maintained through the site

Drainage pipes can be damaged through applying excessive loading (such as construction machinery, material storage and the like). All proposed structures and construction activities are to be sited fully clear of Council drainage pipes, drainage easements, watercourses and trunk overland flow paths on the site. Trunk or dedicated overland flow paths must not be impeded or diverted by fill or structures unless otherwise approved.

If a Council drainage pipeline is uncovered during construction, all work is to cease and the Principal Certifying Authority and Council must be contacted immediately for advice. Any damage caused to a Council drainage system must be immediately repaired in full as directed and at no cost to Council.

**Reason:** To protect existing Council infrastructure and maintain over land flow paths.

#### 68. Erosion control

Temporary sediment and erosion control and measures are to be installed prior to the commencement of any works on the site. These measures must be maintained in working order during construction works up to completion. All sediment traps must be cleared on a regular basis and after each major storm and/or as directed by the Principal Certifying Authority and Council officers.

**Reason:** To protect the environment from erosion and sedimentation.

#### 69. Drainage to street

Stormwater runoff from all new impervious areas and subsoil drainage systems

shall be piped to the street drainage system. New drainage line connections to the street drainage system shall conform and comply with the requirements of Sections 5.3 and 5.4 of Ku-ring-gai Water Management Development Control Plan No. 47.

**Reason:** To protect the environment.

# 70. Grated drain at garage

A 200mm wide grated channel/trench drain, with a heavy-duty removable galvanised grate is to be provided in front of the garage door/basement parking slab to collect driveway runoff. The channel drain shall be connected to the main drainage system and must have an outlet of minimum diameter 150mm to prevent blockage by silt and debris.

Reason: Stormwater control.

### 71. Sydney Water Section 73 Compliance Certificate

The applicant must obtain a **Section 73 Compliance Certificate** under the *Sydney Water Act 1994*. An application must be made through an authorised Water Servicing Co-ordinator. The applicant is to refer to "Your Business" section of Sydney Water's web site at <a href="https://www.sydneywater.com.au">www.sydneywater.com.au</a> then the "edevelop" icon or telephone 13 20 92. Following application a "Notice of Requirements" will detail water and sewer extensions to be built and charges to be paid. Please make early contact with the CoOrdinator, since building of water/sewer extensions can be time consuming and may impact on other services and building, driveway or landscape design.

**Reason:** Statutory requirement.

# 72. Arborist's report

The trees to be retained shall be inspected, monitored and treated by a qualified arborist during and after completion of development works to ensure their long term survival. Regular inspections and documentation from the arborist to the Principal Certifying Authority are required at the following times or phases of work:

### **Schedule**

No/Tree/location

# 5/Juniperus sp. (Juniper)

Adjacent to the site's central rear boundary.

6/*Juniperus sp.* (Juniper)

Adjacent to the site's central rear boundary.

16/Araucaria cunninghamii (Hoop Pine) Close to the site's south-eastern corner.

18/*Liquidambar styraciflua* (Liquidambar)
Close to the eastern end of the site's Stanley Street

#### Time of inspection

Demolition, excavation, drainage and landscape stages.

Demolition, excavation, drainage and landscape

stages.

Demolition, excavation, drainage and landscape stages.

Demolition, excavation, drainage and landscape

#### **KU-RING-GAI PLANNING PANEL**

# Schedule No/Tree/location

boundary.

19/*Franklinia axillaris* (Gordonia)

Adjacent to the site's central Stanley Street boundary.

20/*Hymenosporum flavum* (Native Frangipani) Adjacent to the site's central Stanley Street boundary.

21/*Cedrus deodara* (Himalayan Cedar Adjacent to the site's central Stanley Street boundary.

22/ Jacaranda mimosifolia (Jacaranda)
Adjacent to the site's central Stanley Street boundary.

23/*Magnolia x soulangiana* (Magnolia) Adjacent to the site's central Stanley Street boundary.

24/ Magnolia x soulangiana (Magnolia)
Adjacent to the site's central Stanley Street boundary.

25/Rhododendron sp. (Broad leaf Rhododendron) Adjacent to and near the western end of the site's Stanley Street boundary.

35/*Camellia sasanqua* (Chinese Camellia) Adjacent to the site's north-eastern corner.

Row of *Camellia japonica* (Japanese Camellia) Site's western boundary.

Time of inspection stages.

Demolition, excavation, drainage and landscape stages.

**Reason:** To ensure protection of existing trees.

#### 73. Temporary groundcover

On disturbed areas which will otherwise remain exposed for more than fourteen (14) days before permanent stabilisation works are undertaken, a temporary cover of mulch shall be applied or a dense cover crop shall be established utilising sterile/non seed-setting species.

**Reason:** To protect the environment.

#### 74. Treatment of tree roots

If tree roots are required to be severed for the purposes of constructing the approved works, they shall be cut cleanly by hand, by an experienced arborist/horticulturist with a minimum qualification of horticulture certificate or tree surgery certificate

**Reason:** To protect existing trees.

### 75. No storage of materials beneath trees

No storage or disposal of materials shall take place beneath the canopy of any tree protected under Council's Tree Preservation Order at any time.

**Reason:** To protect existing trees.

#### 76. Tree planting on nature strip

The following tree species shall be planted, at no cost to Council, in the nature strip fronting the property along (enter street). The tree(s) used shall be a minimum 25 litres container size specimen(s):

Schedule		
Tree/species	Quantity	Location
Syncarpia glomulifera (Turpentine)	4	In the Stanley Street nature strip.

**Reason:** To provide appropriate landscaping within the streetscape.

#### 77. Removal of refuse

All builders' refuse, spoil and/or material unsuitable for use in landscape areas shall be removed from the site on completion of the building works.

**Reason:** To protect the environment.

### 78. Canopy replenishment trees to be planted

The 8 canopy replenishment trees to be planted shall be maintained in a healthy and vigorous condition until they attain a height of 5.0 metres whereby they will be protected by Council's Tree Preservation Order. Any of the trees found faulty, damaged, dying or dead shall be replaced with the same species

**Reason:** To maintain the treed character of the area.

# 79. Removal of noxious plants & weeds

The following noxious and/or environmental weed species shall be removed from the property prior to completion of building works:

# Schedule

#### Plant species

Araujia hortorum (Moth Vine)
Asparagus densiflorus (Asparagus Fern)
Asparagus plumosus (Climbing Asparagus)
Chlorophytum comosum (Spider Plant)
Cinnamomum camphora (Camphor laurel)
Cytisus sp. (Broom)
Erigeron karvinskianus (Seaside Daisy)
Hedera helix (English Ivy)
Impatiens balsamina (Impatiens)
Jasminum polyanthum (Jasminum)

# Schedule Plant species

Ligustrum sinense (Small-leaved Privet)
Nephrolepis cordifolia (Fishbone fern)
Ochna serrulata (Ochna)
Rubus fruticosus (Blackberry)
Tradescantia albiflora

**Reason:** To protect the environment.

# CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE:

### 80. Compliance with BASIX Certificate

Prior to the issue of an Occupation Certificate, the Principal Certifying Authority shall be satisfied that all commitments listed in BASIX Certificate No. 166389M have been complied with.

**Reason:** Statutory requirement.

#### 81. Mechanical ventilation

Following completion, installation and testing of all the mechanical ventilation systems, the Principal Certifying Authority shall be satisfied of the following prior to the issue of any Occupation Certificate:

- 1. The installation and performance of the mechanical systems complies with:
  - The Building Code of Australia
  - Australian Standard AS1668
  - Australian Standard AS3666 where applicable
- 2. The mechanical ventilation system in isolation and in association with other mechanical ventilation equipment, when in operation will not be audible within a habitable room in any other residential premises before 7am and after 10pm Monday to Friday and before 8am and after 10pm Saturday, Sunday and public holidays. The operation of the unit outside these restricted hours shall emit a noise level of not greater than 5dbA above the background when measured at the nearest adjoining boundary.

**Note:** Written confirmation from an acoustic engineer that the development achieves the above requirements is to be submitted to the Principal Certifying Authority prior to the issue of the Occupation Certificate.

**Reason:** To protect the amenity of surrounding properties.

# 82. Completion of landscape works

Prior to the release of the Occupation Certificate, the Principal Certifying Authority is to be satisfied that all landscape works, including the removal of all noxious and/or environmental weed species, have been undertaken in accordance with the approved plan(s) and conditions of consent.

**Reason:** To ensure that the landscape works are consistent with the development consent.

#### 83. Retention and re-use positive covenant

Prior to issue of the Occupation Certificate, the applicant must create a positive covenant and restriction on the use of land under Section 88E of the Conveyancing Act 1919, burdening the property with the requirement to maintain the site stormwater retention and re-use facilities on the property.

The terms of the instruments are to be generally in accordance with the Council's "draft terms of Section 88B instruments for protection of retention and re-use facilities" and to the satisfaction of Council (refer to appendices of Ku-ring-gai Water Management Development Control Plan No. 47). For existing titles, the positive covenant and the restriction on the use of land is to be created through an application to the Land Titles Office in the form of a request using forms 13PC and 13RPA. The relative location of the reuse and retention facility, in relation to the building footprint, must be shown on a scale sketch, attached as an annexure to the request forms.

Registered title documents showing the covenants and restrictions must be submitted to and approved by the Principal Certifying Authority prior to issue of an Occupation Certificate.

**Reason:** To protect the environment.

#### 84. Provision of copy of OSD designs if Council is not the PCA

Prior to issue of the Occupation Certificate, the following must be provided to Council's Development Engineer:

- a copy of the approved Construction Certificate stormwater detention/retention design for the site
- A copy of any works-as-executed drawings required by this consent
- The Engineer's certification of the as-built system.

**Reason:** For Council to maintain its database of as-constructed on-site stormwater detention systems.

#### 85. Certification of drainage works

Prior to issue of the Occupation Certificate, the Principal Certifying Authority is to be satisfied that:

- the stormwater drainage works have been satisfactorily completed in accordance with the approved Construction Certificate drainage plans
- the minimum retention and on-site detention storage volume requirements of BASIX and Ku-ring-gai Water Management Development Control Plan No. 47 respectively, have been achieved

- retained water is connected and available for use
- basement and subsoil areas are able to drain via a pump/sump system installed in accordance with AS3500.3 and Appendix 7.1.1 of Ku-ring-gai Water Management Development Control Plan No. 47
- all grates potentially accessible by children are secured
- components of the new drainage system have been installed by a licensed plumbing contractor in accordance with the Plumbing and Drainage Code AS3500.3 2003 and the Building Code of Australia
- all enclosed floor areas, including habitable and garage floor levels, are safeguarded from outside stormwater runoff ingress by suitable differences in finished levels, gradings and provision of stormwater collection devices

The rainwater certification sheet contained in Appendix 13 of the Ku-ring-gai Water Management Development Control Plan No. 47, must be completed and attached to the certification. Where an on-site detention system has been constructed, the on-site detention certification sheet contained in Appendix 4 of DCP 47 must also be completed and attached to the certification.

**Note:** Evidence from a qualified and experienced consulting civil/hydraulic

engineer documenting compliance with the above is to be provided

to Council prior to the issue of an Occupation Certificate.

**Reason:** To protect the environment.

# 86. WAE plans for stormwater management and disposal (dual occupancy and above)

Prior to issue of the Occupation Certificate, a registered surveyor must provide a works as executed survey of the completed stormwater drainage and management systems. The survey must be submitted to and approved by the Principal Certifying Authority prior to issue of the Occupation Certificate. The survey must indicate:

- as built (reduced) surface and invert levels for all drainage pits
- gradients of drainage lines, materials and dimensions
- as built (reduced) level(s) at the approved point of discharge to the public drainage system
- as built location and internal dimensions of all detention and retention structures on the property (in plan view) and horizontal distances to nearest adjacent boundaries and structures on site
- the achieved storage volumes of the installed retention and detention storages and derivative calculations
- as built locations of all access pits and grates in the detention and retention system(s), including dimensions
- the size of the orifice or control fitted to any on-site detention system
- dimensions of the discharge control pit and access grates
- the maximum depth of storage possible over the outlet control
- top water levels of storage areas and indicative RL's through the overland flow path in the event of blockage of the on-site detention system

The works as executed plan(s) must show the as built details above in

comparison to those shown on the drainage plans approved with the Construction Certificate prior to commencement of works. All relevant levels and details indicated must be marked in red on a copy of the Principal Certifying Authority stamped construction certificate stormwater plans.

**Reason:** To protect the environment.

# 87. Basement pump-out maintenance

Prior to issue of the Occupation Certificate, the Principal Certifying Authority shall be satisfied that a maintenance regime has been prepared for the basement stormwater pump-out system.

**Note:** A maintenance regime specifying that the system is to be regularly

inspected and checked by qualified practitioners is to be prepared by a suitable qualified professional and provided to the Principal

Certifying Authority.

**Reason:** To protect the environment.

# 88. OSD positive covenant/restriction

Prior to issue of the Occupation Certificate, the applicant must create a positive covenant and restriction on the use of land under Section 88E of the Conveyancing Act 1919, burdening the owner with the requirement to maintain the on-site stormwater detention facilities on the lot.

The terms of the instruments are to be generally in accordance with the Council's "draft terms of Section 88B instrument for protection of on-site detention facilities" and to the satisfaction of Council (refer to appendices of Kuring-gai Council Water Management DCP 47). For existing titles, the positive covenant and the restriction on the use of land is to be created through an application to the Land Titles Office in the form of a request using forms 13PC and 13RPA. The relative location of the on-site detention facility, in relation to the building footprint, must be shown on a scale sketch, attached as an annexure to the request forms.

Registered title documents, showing the covenants and restrictions, must be submitted and approved by the Principal Certifying Authority prior to issue of an Occupation Certificate.

**Reason:** To protect the environment.

# 89. CCTV report of pipe after work

Prior to issue of the Occupation Certificate, a closed circuit television inspection and report on the Council drainage pipeline traversing the site is to be undertaken by appropriate contractors and provided to Council's Development Engineer. The report is to include a copy of the footage of the inside of the pipeline. Any damage that has occurred to the section of the pipeline since the commencement of construction on the site must be repaired in full to the satisfaction of Council's Development Engineer at no cost to Council.

**Reason:** To protect the environment.

### 90. Sydney Water Section 73 Compliance Certificate

Prior to issue of an Occupation Certificate the Section 73 Sydney water Compliance Certificate must be obtained and submitted to the Principal Certifying Authority

**Reason:** Statutory requirement.

# 91. Certification of as-constructed driveway/car park – RFB

Prior to issue of an Occupation Certificate, the Principal Certifying Authority is to be satisfied that:

- the as-constructed car park complies with the approved Construction Certificate plans
- the completed vehicle access and accommodation arrangements comply with Australian Standard 2890.1 – 2004 "Off-Street car parking" in terms of minimum parking space dimensions
- finished driveway gradients and transitions will not result in the scraping of the underside of cars
- no doors, gates, grilles or other structures have been provided in the access driveways to the basement car park, which would prevent unrestricted access for internal garbage collection from the basement garbage storage and collection area
- the vehicular headroom requirements of:
  - Australian Standard 2890.1 "Off-street car parking",
  - 2.44 metres height clearance for waste collection trucks (refer DCP 40) are met from the public street into and within the applicable areas of the basement car park.

**Note:** Evidence from a suitably qualified and experienced traffic/civil engineer indicating compliance with the above is to be provided to and approved by the Principal Certifying Authority prior to the issue

of an Occupation Certificate.

**Reason:** To ensure that vehicular access and accommodation areas are

compliant with the consent.

# 92. Reinstatement of redundant crossings and completion of infrastructure works

Prior to issue of the Occupation Certificate, the Principal Certifying Authority must be satisfied that the following works in the road reserve have been completed:

- new concrete driveway crossing in accordance with levels and specifications issued by Council
- removal of all redundant driveway crossings and kerb laybacks (or

sections thereof) and reinstatement of these areas to footpath, turfed verge and upright kerb and gutter (reinstatement works to match surrounding adjacent infrastructure with respect to integration of levels and materials)

- full repair and resealing of any road surface damaged during construction
- full replacement of damaged sections of grass verge with a non-friable turf of native variety to match existing

All works must be completed in accordance with the General Specification for the Construction of Road and Drainage Works in Ku-ring-gai Council, dated November 2004. The Occupation Certificate must not be issued until all damaged public infrastructure caused as a result of construction works on the subject site (including damage caused by, but not limited to, delivery vehicles, waste collection, contractors, sub contractors, concrete vehicles) is fully repaired to the satisfaction of Council. Repair works shall be at no cost to Council.

**Reason:** To protect the streetscape.

# 93. Fire safety certificate

Prior to the issue of the Occupation Certificate, the Principal Certifying Authority shall be satisfied that a Fire Safety Certificate for all the essential fire or other safety measures forming part of this consent has been completed and provided to Council.

**Note:** A copy of the Fire Safety Certificate must be submitted to Council.

**Reason:** To ensure suitable fire safety measures are in place.

# CONDITIONS TO BE SATISFIED PRIOR TO THE ISSUE OF A SUBDIVISION CERTIFICATE:

# 94. Easement for waste collection

Prior to issue of the Occupation Certificate, an easement for waste collection is to be created under Section 88B of the Conveyancing Act 1919. This is to permit legal access for Council, Council's contractors and their vehicles over the subject property for the purpose of collecting waste from the property. The terms of the easement are to be generally in accordance with Council's draft terms for an easement for waste collection and shall be to the satisfaction of Council's Development Engineer.

**Reason:** To permit legal access for Council, Council's contractors and their vehicles over the subject site for waste collection.

#### CONDITIONS TO BE SATISFIED AT ALL TIMES:

#### 95. No door restricting internal waste collection in basement

At all times, the basement garbage storage and collection area is to be accessible by Council's Waste Collection Services. No doors, grilles, gates or

other devices shall be provided in any location which would prevent this service. Where a gate, door or the like is to be erected, unimpeded access to the garbage collection point is to be provided by other means through written agreement with Council's Waste Collection Services.

**Reason:** To facilitate access to the garbage collection point.

# 96. Noise control – plant and machinery

All noise generating equipment associated with any proposed mechanical ventilation system/s shall be located and/or soundproofed so the equipment is not audible within a habitable room in any other residential premises before 7am and after 10pm Monday to Friday and before 8am and after 10pm Saturday, Sunday and public holidays. The operation of the unit outside these restricted hours shall emit a noise level of not greater than 5dbA above the background when measured at the nearest boundary.

**Reason:** To protect the amenity of surrounding residents.

### 97. Car parking

At all times, the visitor car parking spaces are to be clearly identified and are to be for the exclusive use of visitors to the site. On site permanent car parking spaces are not to be used by those other than an occupant or tenant of the subject building. Any occupant, tenant, lessee or registered proprietor of the development site or part thereof shall not enter into an agreement to lease, license or transfer ownership of any car parking spaces to those other than an occupant, tenant or lessee of the building.

These requirements are to be enforced through the following:

- restrictive covenant placed on title pursuant to Section 88B of the Conveyancing Act, 1919
- restriction on use under Section 68 of the Strata Schemes (Leasehold Development) Act, 1986 to all lots comprising in part or whole car parking spaces

**Reason:** To ensure adequate provision of visitor parking spaces.

# 98. Unobstructed driveways and parking areas

At all times, all driveways and parking areas shall be unobstructed. Driveways and car spaces shall not be used for the manufacture, storage or display of goods, materials or any other equipment and shall be used solely for vehicular access and for the parking of vehicles associated with the use of the premises.

**Reason:** To ensure safe traffic movement.

**CARRIED UNANIMOUSLY** 

The Meeting closed at 5.13pm

The Minutes of the Ku-ring-gai Planning Panel held on 30 April 2008 (Pages 1 - 59) were confirmed as a full and accurate record of proceedings on 14 May 2008.

Chairperson	